

MN/DOT GEODETIC DATABASE

STATION NAME: **9219** NGS/ QUAD/STA # _____/____

COUNTY: **RAMSEY** MAP SHT/INDEX # ___/___ NGS ACRN # _____

SE1/4	SEC	TWP	RNG	LATITUDE	LONGITUDE	GPS	USGS QUAD MAP
SE	22	30	22				
				AGENCY	YR-SET	YR-REC	COND
				<u>R.C.P.W</u>	<u>2005</u>	_____	_____
							PHYS
							BRDG

DESCRIPTION: (2005)
 In the city of Gem Lake at the intersection of Co. Rd. F and Hoffman Rd. 18' north of the centerline of Co. Rd. F extended, 25.2' west of the Westerly fog line (white line) of Hoffman Rd., 47.3' from the face of a guy power pole, and 73.6' south of the face of the high tension pole, and 1' east of the sign post.

The USGS Quad Map is recommended as an aid when recovering this station.

ELEVATIONS		ADJUSTMENT		
NGVD 29	NAVD 88	YEAR	ORDER	METHOD REFERENCE
	<u>928.177</u>	<u>2005</u>		

MN ZONE: _____ SPEC COUNTY ZONE: _____

COORDINATES		GEODETIC POSITIONS		ADJUSTMENT	
X	Y	LATITUDE	LONGITUDE	YEAR	REFERENCE
NAD27: _____	_____	_____	_____	_____	_____
NAD83: _____	_____	_____	_____	_____	_____

COUNTY: **591681.7G** **200000.4G** _____

COORDINATES IN 1991 ADJUSTMENT VALUES. FOR LOCATION PURPOSES ONLY

___/___/___ entered
 ___/___/___ modified