MONUMENT 231

CERTIFICATE OF LOCATION OF SECTION SUBDIVISION MONUMENT

Center of Section 28, Township 30 North, Range 23 West, County of Ramsey, State of Minnesota.

| of Minnesota. At the corner location shown on the sketch | |
|---|---|
| | nonument with drill hole, up 0.25 ft. |
| ☐ On placed a | monument removed monument (explain) |
| Nail and Ramsey County disk in 30 in. Oak, up 1.5 ft. S57'30'46"W 19.28 — — Nail and Ramsey County disk in 6 in. Box Elder, up 4.0 ft. N03'38'18"W 11.93 Ramsey County Up 4.0 ft. N03'38'18"W 11.93 Ramsey County Bench Mark No. 9088 Punch mark top nut of hydrant | |
| RAMSEY COUNTY NAD83 (1986) MONUMENT 231 X= 553128.240 (Easting) | Punch mark top nut of hydrant ALL DISTANCES ARE SHOWN IN U.S. SURVEY FEET. |
| Y= 197157.913 (Northing) | BEARINGS ARE FOR TIE REFERENCE PURPOSES ONLY. |
| Statements of evidence relative to this corner are on the following page. | |
| I hereby certify that this document was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota. Daniel D. Baar Date | OFFICE OF COUNTY SURVEYOR County of Ramsey I hereby certify that this document was filed in the County Surveyor's office this day of, 20 |
| Minnesota License No. 45816 ☐ County Surveyor ☐ Deputy County Surveyor ☐ Land Surveyor | Craig W. Hinzman, L.S. Ramsey County Surveyor |

MONUMENT 231

| Fixed Center of Section 28 by intersection and set monument, December, 1900. | |
|--|--|
| Found a granite monument up 3 in. and tied, September 24, 1974. | |
| Retied monument; set sign and post +/-2 ft. west of monument, January 7, 1992. | |
| Retied monument, November 25, 1998. | |
| Retied monument, October 17, 2005. | |
| Retied granite monument with drill hole, up 0.25 ft., October 21, 2011. | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |