MONUMENT 299

CERTIFICATE OF LOCATION OF SECTION SUBDIVISION MONUMENT

Center of Section 36, Township 30 North, Range 22 West, County of Ramsey, State of Minnesota.

of Minnesota. At the corner location shown on the sketch	
☑ On August 15, 2011 found a cast iron	monument, flush.
☐ On placed a	monument removed monument (explain)
SKETCH OF RECONSIDERAL SIDE ORCHARD LANE	P.K. nail in concrete curb expansion joint N11°57'02"W
Ramsey County Bench Mark No. 9238 S87'24'22"W 28.30 — — Northwest top corner of electrical panel box, up 5.5 ft. S74'50'30"W 43.05 — —	Punch mark top nut of hydrant N81*45'00"E 7 - 26.37
RAMSEY COUNTY NAD83 (1986) Monument 299 Nail and Ramsey County disk in 18 in. Ash, up 5 ft.	BELLAIRE
X= 600394.278 (Easting) Y= 192084.594 (Northing)	ALL DISTANCES ARE SHOWN IN U.S. SURVEY FEET. BEARINGS ARE FOR TIE REFERENCE PURPOSES ONLY.
Statements of evidence relative to this corner are on the following page.	
I hereby certify that this document was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota. Daniel D. Baar Date	OFFICE OF COUNTY SURVEYOR County of Ramsey I hereby certify that this document was filed in the County Surveyor's office this day of, 20
Minnesota License No. 45816 ☐ County Surveyor ☐ Land Surveyor	Craig W. Hinzman, L.S. Ramsey County Surveyor

MONUMENT 299

Fixed the Center of Section 36 by intersection and set monument, November 19, 1900.

Found 1/2 in. pipe over a granite monument. Granite monument down 0.45 ft., May 28, 1974.

Placed a short (4-1/2 in.) cast iron monument on top of granite monument, November 7, 1974.

Re-cemented cast iron monument, May 20, 1975.

Tied monument, June 15, 1990.

Removed monument for Maintenance Department, May 3, 1994.

Relocated position with P.K. nails, May 9, 1996.

Placed a 20 in. cast iron monument, 1996.

Tied monument, September 30, 1999.

Retied monument, August 30, 2006.

Retied cast iron monument, flush, August 15, 2011.