



Oak 6" 96.70

2623.3

2623.64

FP 38.55

34.32 F.P.

M.C. No 9

SNAIL LAKE

24

2613.32

2528.66
2644.14

808.94

M.C. No 10

1750.0

2632.06

2632.42

tree 10" 34.67

tree 8" 21.27
tree 15" 21.00

tree 10" 53.88
tree 12" 71.10
tree 24" 44.92
tree 73' 65.10
tree 53.46
350

tree 4" wo 43.15
tree 17.97
92.80 T.P.

2641.44

1831.50

2627.38

LAKE

2613.32

tree 65.63
tree 37.96

tree 10.59

2641.20

cotton wood 35.72

86.40 08"

2641.20

57.45

03"

43.44
scrub oak
32.18 T.P.

59.41
15" 80
46.67 O.F.P.
63.16 019" oak

tree 20" 37.38
tree 8" 130
tree 14" 38.57

19' oak

6' oak

RICE

In Establishing the $\frac{1}{4}$ Corner between Sections 13 and 24 Found one Gov. witness tree
and one Gov. witness stump Fixed Corner tied it and set Mount.
July - 1896

In Establishing the North East Corner of Section 24 Found old stake at
Section Corner Gov. witness trees gone Fixed Corner tied it and set Mount.
in Apr. 1895

In Establishing the $\frac{1}{4}$ Corner between Sections 24 T 30 R 23 and Section 19 T 30 R 22
Measured the distance from South East Corner of Section 24 to North East Corner
of Section 24 and fixed the $\frac{1}{4}$ Corner half way Gov. witness trees gone
June 1896 Set Mount. Aug 9 - 1897

In Establishing the South East Corner of Section 24 This Corner was fixed from
Iron stake found at Block Corner. Gov. witness trees gone set Mount.
Apr. 1895 found old stake at Sec. Cor.

In Establishing the South West Corner of Section 24 Measured East from
Mount. at $\frac{1}{4}$ Cor. between Sections 23 and 26. 2641.40 which appeared
to be about correct according to all evidences. Gov. witness trees gone
Fixed Corner tied it and set Mount. Dec. 5 - 1896.

The North West Cor. of Section 24 was fixed by using Gov. distance from
Meadow Cor. No 9 Gov. witness trees gone
Set Mount. Oct. 28, 1897

Meadow Cor. No 9 was fixed from Gov. witness trees
Set Mount. Oct. 28 - 1897

Meadow Cor. No 10 was fixed by using Gov. distance from Section Cor.
Gov. witness trees gone Set Mount. Oct. 28 - 1897

Fixed $\frac{1}{4}$ Cor. between Sections 23 & 24 Jan 28 1898 in Snail Lake.

In Establishing the $\frac{1}{4}$ Cor. between Section 24 & 25 Run straight line from Cor. to
Cor. and fixed $\frac{1}{4}$ Cor. $\frac{1}{2}$ way Gov. trees gone Jan 21 - 1899 Set Mount. Nov. 1899

Fixed the Center of Sec. 24 by Intersection March 9 - 1899
Set Mount. Nov. 1899