

In Establishing the South west Cor. of Section 26. This Cor. was fixed by
Measuring North from Cor. found on Town line 1 mile ^{found} over Gov. witness stump
Fixed Cor. tied it and set Mount. Oct. - 1895

In Establishing the $\frac{1}{4}$ Cor. between Sections 26 and 27 Measured North from Section
Cor. 2640 Gov. witness tree gone Fixed Cor. tied it and set Mount.
Oct. - 1895

In Establishing the North West Cor. of Section 26 Measured North from $\frac{1}{4}$ Cor.
2640 Gov. witness tree gone Fixed Cor. tied it and set Mount.
Oct. 1895 found old stake.

In Establishing the $\frac{1}{4}$ Cor. between Section 23 and 26 Found old stake at
 $\frac{1}{4}$ Cor. Gov. witness tree gone Fixed Cor. tied it and set Mount.
Nov. 4 - 1895

In Establishing the North East Cor. of Section 26 Measured East from
Mount at $\frac{1}{4}$ Cor. between Section 23 and 26 2641.40 which appeared to
be about correct according to all evidences Gov. witness tree gone
Fixed Cor. tied it and set Mount. Dec. 8 - 1896

In Establishing the $\frac{1}{4}$ Cor. between Section 25 and 26 found old stake Gov.
witness tree gone Fixed Cor. tied it and set Mount. July 28 1897

The South East Cor. of Section 26 was fixed July 29 - 1897 Set Mount.

The $\frac{1}{4}$ Cor. between Section 26 and 35 was fixed by running a straight line which point
is 52.03 South of the South Rail of Railroad track in Lake no Gov. trees
July 26 - 1897

Fixed the Center of Sec 26 Aug 4 - 1897 and set Mount.