

## **GENERAL SITE PLAN NOTES:**

CONTRACTOR SHALL FIELD VERIFY THE LOCATIONS AND ELEVATIONS OF EXISTING UTILITIES AND TOPOGRAPHIC CONDITIONS PRIOR TO CONSTRUCTION START. THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE LANDSCAPE ARCHITECT OF ANY DISCREPANCIES OR VARIATIONS FROM THE PLANS. ANY DISCREPANCIES FOUND THAT AFFECT THE WORK SHALL BE REPORTED TO THE OWNER or OWNER'S REPRESENTATIVE FOR CLARIFICATION PRIOR TO ANY ADDITIONAL WORK BEING COMPLETED.

CONTRACTOR SHALL CONTACT "GOPHER STATE ONE CALL" FOR ALL UTILITY LOCATIONS (651-454-0002) 48 HR. PRIOR TO EXCAVATION/CONSTRUCTION.

CONTRACTOR TO VERIFY HORIZONTAL LOCATION AND ELEVATION WHERE A CONNECTION TO EXISTING PAVEMENT, STRUCTURE OR SITE FEATURE IS TO

CONTRACTOR TO WORK OUT OF TREE DRIP ZONE EXCEPT IN AREAS

CRITICAL LAYOUT DIMENSIONS: THE OWNER OR OWNER'S REPRESENTATIVE RESERVES THE RIGHT TO REVISE THE PROJECT LAYOUT TO AVOID UNFORESEEN CONSTRAINTS SUCH AS MATURE TREES, UNFORESEEN SOIL CONTACT INFORMATION: CONSTRAINTS, ETC. THESE ADJUSTMENTS SHALL BE CONSIDERED

CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING EXISTING UTILITIES, brett.blumer@co.ramsey.mn.us 651.748.2500 TREES, SITE AMENITIES, ETC. FROM DAMAGE DURING CONSTRUCTION.

CONTRACTOR SHALL BE RESPONSIBLE FOR CORRECTING ANY DAMAGE (AT I hereby certify that this plan, ALL LOCATES LOCATES SHALL BE MARKED IN THE FIELD FOR REVIEW BY THE me or under my direct supervision and that I am a duly Licensed Landscape OWNER OR OWNER'S REPRESENTATIVE.

CONTRACTOR SHALL STAY WITHIN CONSTRUCTION LIMITS UNLESS APPROVED | Registration: Landscape Architect OTHERWISE BY THE OWNER OR OWNERS REPRESENTATIVE. THE WORK ZONE | State SHALL BE KEPT AS MINIMAL AS POSSIBLE DURING CONSTRUCTION. MOVEMENT AND PARKING OF EQUIPMENT SHALL STAY WITHIN WORK ZONE AND NOT CROSS AREAS OTHERWISE UNDISTURBED DURING EARTHWORK

LAYOUT NOTES: BITUMINOUS TRAIL, CONCRETE CURBS, AND CONSTRUCTION 1 5/22/18 BID DOCUMENTS LIMITS SHALL BE FIELD STAKED BY CONTRACTOR. CONTRACTOR WILL NEED APPROVAL BY RAMSEY COUNTY LANDSCAPE ARCHITECT PRIOR TO COMMENCING CONSTRUCTION. CONTRACT ITEMS LAID OUT AND INSTALLED INCORRECTLY WITHOUT PRIOR REVIEW BY RAMSEY COUNTY REPRESENTATIVE WILL BE REMOVED AND REINSTALLED AT CONTRACTORS

SPOT GRADES & DRAINAGE REQUIREMENTS: ALL SPOT ELEVATIONS REPRESENT FINISHED SURFACE GRADE UNLESS OTHERWISE NOTED.

THE CONTRACTOR SHALL REVIEW GRADING WITH THE LA-ENG.. PRIOR TO EARTHWORK TO ENSURE PROPER DRAINAGE. THE INTENT OF ALL PROPOSED SPOT GRADES AND GRADING IS TO MATCH EXISTING GRADES ADJACENT TO NEW CONSTRUCTION TO ENSURE PROPER DRAINAGE AND BLENDING OF NEW GRADES WITH EXISTING ONES. MAX.. SLOPES SHALL NOT BE GREATER THAN 4:1 UNLESS OTHERWISE NOTED ON THE PLAN.

SUB CUT REQUIREMENTS: GRADES AS SHOWN ARE TO FINISH GRADE. CONTRACTOR SHALL SUB CUT IN ACCORDANCE WITH PAVEMENT SECTIONS.

CONTRACTOR SHALL BE RESPONSIBLE FOR ANY SURVEYING RELATING TO LAYOUT & SITE GRADING. THE CONTRACTOR SHALL FIELD VERIFY ALL GRADES WITH THE LANDSCAPE ARCHITECT PRIOR TO CONSTRUCTION. CONTRACTOR SHALL NOTIFY OWNER OF ANY DISCREPANCIES OR VARIATION

<u>TOPSOIL STRIPPING, STOCKPILING AND RE-SPREADING REQUIREMENTS:</u> TOPSOIL SHALL BE STRIPPED FROM ALL DISTURBED AREAS FROM COMMON EXCAVATION AND SHALL BE SALVAGED AND STOCKPILED. THE LANDSCAPE ARCHITECT SHALL DETERMINE PLACEMENT OF THE STOCKPILE PRIOR TO

EXISTING TOPSOIL FROM COMMON EXCAVATION SHALL BE SALVAGED AND STOCKPILED IN A TEMPORARY STORAGE AREA. SALVAGED TOPSOIL SHALL BE FREE OF CONTAMINANTS & DEBRIS ROOTS, WEEDS AND ROCK OVER ½" IN SIZE

CONTRACTOR SHALL STRIP, STOCKPILE & RE-SPREAD SUFFICIENT TOPSOIL PROVIDE A MINIMUM 4 INCH DEPTH (COMPACTED) TO ALL DISTURBED AREAS T $^{\circ}$ BE RESTORED. UNLESS OTHERWISE NOTED. SALVAGED TOPSOIL SHALL NOT BE USED FOR THE TEE BOX RESTORATION, SEE SPECIFICATIONS. ALL DISTURBED AREAS TO RECEIVED SEED/TURF ESTABLISHMENT AND ADD SOIL AMENDMENTS FOR OPTIMUM PLANT GROWTH. TOPSOIL SHALL BE IN A RELATIVELY DRY STATE WHEN PLACED. FINE GRADE TOPSOIL TO ELIMINATE ROUGH OR LOW SPOTS. MANUALLY SPREAD TOPSOIL CLOSE TO TREES,

EXCESS STOCKPILE MATERIAL THAT IS NOT SUITEABLE FOR REUSE SHALL BE DISPOSED OFF SITE BY THE CONTRACTOR. THE CONTRACTOR IS RESPONSIBLE FOR RESTORING ALL STOCKPILE AREAS AFTER MATERIAL IS REMOVED.

IMPORTED TOPSOIL SHALL BE PLACED IN AREAS WITH INADEQUATE TOPSOIL AS DETERMINED IN THE FIELD BY OWNER'S REPRESENTATIVE. CLEAN TOPSOIL IMPORT SHALL CONFORM TO MNDOT 3877 TYPE A REQUIREMENTS

<u>SILT AND TREE PROTECTIVE FENCE:</u> CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING SILT FENCE PER PLAN PRIOR TO CONSTRUCTION. SILT FENCE LOCATIONS SHALL BE REVIEWED PRIOR TO CONSTRUCTION.

CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING ALL STORM DRAIN

CONTRACTOR SHALL ERECT AND MAINTAIN PROTECTIVE FENCING FOR EXISTING TREES THAT ARE TO REMAIN AND THAT ARE NEAR THE CONSTRUCTION ZONE. OWNER WILL WALK THE SITE WITH THE CONTRACTOR PRIOR TO ROUGH GRADING TO IDENTIFY TREES TO BE PROTECTED TREE PROTECTION INCLUDING PROTECTIVE FENCING SHALL BE CONSIDERED INCIDENTAL TO THE GRADING WORK AND SHOULD BE INCLUDED IN THE CONTRACTORS BID PRICE FOR THAT WORK REFER TO SPECIFICATIONS FOR

> **CONSTRUCTION LIMITS** SILT FENCE TREE FENCING

PERMEABLE PAVEMENT **BD 3.0** 

SHEET 3 OF 28



COUNTY Parks & Recreation

2015 VAN DYKE STREET

MAPLEWOOD, MN 55109 TEL (651)748-2500

FAX (651)748-2508

B. Gus Blumer

IO. DATE: DESCRIPTION:

DESIGN PHASE: **REVIEW** 

**DOCUMENTS** 

CTICI DJECT REATIC

DECEMBER 2018

DRAWN BY:

SITE PLAN