

CONTRACTOR SHALL FIELD VERIFY THE LOCATIONS AND ELEVATIONS OF EXISTING UTILITIES AND TOPOGRAPHIC CONDITIONS PRIOR TO CONSTRUCTION START. THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE LANDSCAPE ARCHITECT OF ANY DISCREPANCIES OR VARIATIONS FROM THE PLANS. ANY DISCREPANCIES FOUND THAT AFFECT THE WORK SHALL BE REPORTED TO THE OWNER or OWNER'S REPRESENTATIVE FOR CLARIFICATION PRIOR TO ANY ADDITIONAL WORK BEING COMPLETED.

CONTRACTOR SHALL CONTACT "GOPHER STATE ONE CALL" FOR ALL UTILITY LOCATIONS (651-454-0002) 48 HR. PRIOR TO EXCAVATION/CONSTRUCTION.

CONTRACTOR TO VERIFY HORIZONTAL LOCATION AND ELEVATION WHERE A CONNECTION TO EXISTING

CONTRACTOR TO WORK OUT OF TREE DRIP ZONE EXCEPT IN AREAS DESIGNATED BY LANDSCAPE

CRITICAL LAYOUT DIMENSIONS: THE OWNER OR OWNER'S REPRESENTATIVE RESERVES THE RIGHT TO REVISE THE PROJECT LAYOUT TO AVOID UNFORESEEN CONSTRAINTS SUCH AS MATURE TREES, UNFORESEEN SOIL CONSTRAINTS, ETC. THESE ADJUSTMENTS SHALL BE CONSIDERED INCIDENTAL TO THE

CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING EXISTING UTILITIES, TREES, SITE AMENITIES, ETC.

CONTRACTOR SHALL BE RESPONSIBLE FOR CORRECTING ANY DAMAGE (AT CONTRACTORS EXPENSE). THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL LOCATES. LOCATES SHALL BE MARKED IN THE FIELD FOR

CONTRACTOR SHALL STAY WITHIN CONSTRUCTION LIMITS UNLESS APPROVED OTHERWISE BY THE OWNER OR OWNERS REPRESENTATIVE. THE WORK ZONE SHALL BE KEPT AS MINIMAL AS POSSIBLE DURING CONSTRUCTION. MOVEMENT AND PARKING OF EQUIPMENT SHALL STAY WITHIN WORK ZONE AND NOT CROSS AREAS OTHERWISE UNDISTURBED DURING EARTHWORK OPERATION.

CONTRACTOR BASE BID SHALL ASSUME TREES TO BE REMOVED BY RAMSEY COUNTY PRIOR TO CONSTRUCTION. CLEARING, GRUBBING, AND STUMP REMOVAL IS THE RESPONSIBILITY OF THE CONTRACTOR AND SHOULD BE DISPOSED OF OFF SITE. TREES UNDER 6" DIA. SHALL BE INCIDENTAL TO THE GRADING. ASPHALT ROADWAY, PARKING LOTS AND OTHER ITEMS - LAYOUT NOTES: BITUMINOUS TRAIL, CONCRETE CURBS. AND CONSTRUCTION LIMITS SHALL BE FIELD STAKED BY CONTRACTOR. CONTRACTOR WILL NEED APPROVAL BY RAMSEY COUNTY LANDSCAPE ARCHITECT PRIOR TO COMMENCING CONSTRUCTION. CONTRACT ITEMS LAID OUT AND INSTALLED INCORRECTLY WITHOUT PRIOR REVIEW BY RAMSEY COUNTY

SPOT GRADES & DRAINAGE REQUIREMENTS: ALL SPOT ELEVATIONS REPRESENT FINISHED SURFACE GRADE

THE CONTRACTOR SHALL REVIEW GRADING WITH THE LA-ENG.. PRIOR TO EARTHWORK TO ENSURE PROPER DRAINAGE. THE INTENT OF ALL PROPOSED SPOT GRADES AND GRADING IS TO MATCH EXISTING GRADES ADJACENT TO NEW CONSTRUCTION TO ENSURE PROPER DRAINAGE AND BLENDING OF NEW GRADES WITH EXISTING ONES. MAX.. SLOPES SHALL NOT BE GREATER THAN 4:1 UNLESS OTHERWISE NOTED ON THE PLAN.

SUB CUT REQUIREMENTS: GRADES AS SHOWN ARE TO FINISH GRADE. CONTRACTOR SHALL SUB CUT IN

CONTRACTOR SHALL BE RESPONSIBLE FOR ANY SURVEYING RELATING TO LAYOUT & SITE GRADING. THE CONTRACTOR SHALL FIELD VERIFY ALL GRADES WITH THE LANDSCAPE ARCHITECT PRIOR TO CONSTRUCTION. CONTRACTOR SHALL NOTIFY OWNER OF ANY DISCREPANCIES OR VARIATION FROM PLAN.

TOPSOIL STRIPPING, STOCKPILING AND RE-SPREADING REQUIREMENTS: TOPSOIL SHALL BE STRIPPED FROM ALL DISTURBED AREAS FROM COMMON EXCAVATION AND SHALL BE SALVAGED AND STOCKPILED. THE LANDSCAPE ARCHITECT SHALL DETERMINE PLACEMENT OF THE STOCKPILE PRIOR TO CONSTRUCTION.

EXISTING TOPSOIL FROM COMMON EXCAVATION SHALL BE SALVAGED AND STOCKPILED IN A TEMPORARY STORAGE AREA. SALVAGED TOPSOIL SHALL BE FREE OF CONTAMINANTS & DEBRIS ROOTS, WEEDS AND

CONTRACTOR SHALL STRIP, STOCKPILE & RE-SPREAD SUFFICIENT TOPSOIL TO PROVIDE A MINIMUM 4 INCH DEPTH (COMPACTED) TO ALL DISTURBED AREAS TO BE SEEDED, UNLESS OTHERWISE NOTED. ALL DISTURBED AREAS TO RECEIVED SEED/TURF ESTABLISHMENT AND ADD SOIL AMENDMENTS FOR OPTIMUM PLANT GROWTH. TOPSOIL SHALL BE IN A RELATIVELY DRY STATE WHEN PLACED. FINE GRADE TOPSOIL TO ELIMINATE ROUGH OR LOW SPOTS. MANUALLY SPREAD TOPSOIL CLOSE TO TREES, PLANTS, AND PAVEMENT TO PREVENT

EXCESS STOCKPILE MATERIAL THAT IS NOT SUITEABLE FOR REUSE SHALL BE DISPOSED OFF SITE BY THE CONTRACTOR. THE CONTRACTOR IS RESPONSIBLE FOR RESTORING ALL STOCKPILE AREAS AFTER MATERIAL

IMPORTED TOPSOIL SHALL BE PLACED IN AREAS WITH INADEQUATE TOPSOIL AS DETERMINED IN THE FIELD BY OWNER'S REPRESENTATIVE. CLEAN TOPSOIL IMPORT SHALL CONFORM TO MNDOT 3877 TYPE A

SILT AND TREE PROTECTIVE FENCE: CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING SILT FENCE PER PLAN PRIOR TO CONSTRUCTION. SILT FENCE LOCATIONS SHALL BE REVIEWED PRIOR TO CONSTRUCTION.


CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING ALL STORM DRAIN INLETS

CONTRACTOR SHALL ERECT AND MAINTAIN PROTECTIVE FENCING FOR EXISTING TREES THAT ARE TO REMAIN AND THAT ARE NEAR THE CONSTRUCTION ZONE. OWNER WILL WALK THE SITE WITH THE CONTRACTOR PRIOR TO ROUGH GRADING TO IDENTIFY TREES TO BE PROTECTED TREE PROTECTION INCLUDING PROTECTIVE FENCING SHALL BE CONSIDERED INCIDENTAL TO THE GRADING WORK AND SHOULD BE INCLUDED IN THE CONTRACTORS BID PRICE FOR THAT WORK REFER TO SPECIFICATIONS FOR ADDITIONAL INFORMATION.

ALL CURBING SHALL BE MNDOT TYPE D EXCEPT IN THE EXISTING PARKING LOT WHICH HAS EXISTING TYPE B6 CURBING. NEW CURBING IN THE EXISTING PARKING LOT ONLY, SHALL BE TYPE B6 UNLESS OTHERWISE NOTED REFER TO GRADING PLAN FOR CURB TRANSITION FROM TYPE D TO FOR EXISTING PARKING LOT

TAMARACK NATURE CENTER WILL REMAIN OPEN TO THE PUBLIC DURING CONSTRUCTION. THIS INCLUDES THE EARLY LEARNING CENTER PRESCHOOL. THIS MEANS THE PROJECT WILL NEED TO BE CONSTRUCTED IN SUCH A MANNER SO THAT PARKING, VEHICULAR ACCESS, AND PEDESTRIAN ACCESS IS KEPT AVAILABLE AND OPEN

THE CONTRACTOR SHALL ATTEND A PRE CONSTRUCTION MEETING TO BE HELD ON SITE AND SUBMIT A CONSTRUCTION PHASING PLAN PRIOR TO THE START OF THE CONSTRUCTION FOR APPROVAL BY THE OWNER.





COUNTY Parks & Recreation 2015 VAN DYKE STREET

MAPLEWOOD, MN 55109

TEL (651)748-2500 FAX (651)748-2508

pecification or report was prepared by me or under my direct supervision and nat I am a duly Licensed Landscape

Architect under the laws of the State of Landscape Archite

NO. DATE: DESCRIPTION:

4/19/12 BID DOCUMENTS

DESIGN PHASE:

DOCUMENTS

JUNE 2016 DESIGNED BY:

CHECKED BY:

TITLE

SITE PLAN

SHEET 3 OF 30