

		177.53	5		
146	120-40	16.7		60.8	6" Pine
145	117-20	15.5		61.0	4" Pine
142	115-26	16.5		61.0	"
138	116-10	16.3		61.2	"
127	111-2	15.3		62.2	6" Pine
135	102°	15.5		62.0	4" Pine
133	74-40	13.7		63.8	3-6" Plywood
145	76 1/2	14.3		63.2	3" Maple
163	121-10	17.1		60.4	T.B.
171	120-10	19.4		58.1	T.B.
210	115-20	20.1		57.4	B.B.
178	105-40	17.3		58.2	
162	105°	18.7		58.6	"
155	108-40	16.7		60.8	T.B.
166	77-10	14.7		62.8	"
170	122-20	19.4		58.1	T.B.
155	92-20	11.7		65.8	
113	118-40	12.3		65.5	T.B.
97	81-40	11.3		66.5	B.B.
75	121°	11.30		66.23	2" Plywood
66	75°	4.8		72.7	S. end S.W.
48	47-20	4.82		72.71	T.B.

DIETZEN NO. 584-S

	3.100 2.185 2.175	±	St. 100 ft. etc.	177.53 and Cub.	1007	
353	109-40	10.5		67.0		
385	115°	11.4		66.1	T.B.	
387	114 1/2	10.6		66.9	T.B.	
368	109°	10.1		67.9		
360	108-50	10.3		67.2		
357	122°	9.3		68.2		
337	75-40	9.9		68.7		
356	70-30	7.5		70.0	T.C.	
"	"	7.02		70.51	T.C.	
351	84-50	6.82		70.71	2 Md.	
285	76°	6.7		70.8	12" B.C.	
179	91-20	11.6		65.9	12" B.C.	
98	157-40	6.3		71.2	T.B.	
104	162°	6.5		70.7	12" B.C.	
165	163°	12.5		65.0	T.B.	
182	152°	16.5		61.0		
202	142°	18.3		59.2		
235	133-20	20.7		56.8		
265	129-20	20.8		56.7		
240	121-20	20.6		56.9		
208	127 1/2	19.6		57.9		