

		177.53			
187	71°	10.5	67.2	B&E FKH	
190	92-10	8.1	69.4		
190	103-30	7.9	67.6		
189	100-10	10.4	67.1	7.5	
229	142-30	12.4	66.6		
225	117-40	12.5	66.9		
250	108-40	10.2	67.3		
240	99 1/2	10.5	67.0		
233	91° 40'	9.3	68.2	BM	
	92°	"	68.2	12" 6/10	
233	88-30	5.8	71.7		
237	82-10	6.66	70.87		
	"	7.01	70.52	B.C.	
238	82-15	6.32	71.21	B.P.	
273	83-15	6.55	70.98		
271	87-50	7.17	70.36		
	"	6.91	70.62		
275	88-50	5.2	71.3		
275	92-10	7.8	68.7	2-12' 30"	
276	91°	7.6	67.9	BB	
281	97-10	10.2	67.3		

Track	Lev	177.53 about 137.	at	Meas.
80	155°	6.8	71.0	TB
51	139 1/2	5.3	72.2	
44	155 1/2	5.5	72.0	
22	161	6.0	71.5	E.P.
40	180	5.34	72.19	
	N. 1/2	5.40	172.13	
16	142 1/2	5.48	72.07	P.C. 2nd
"	"	5.25	72.28	B. End 40'
28	124°	4.9	72.6	N.S. 20' 15'
33	113°	5.6	71.9	24" 2nd
25	70 1/2	5.58	71.95	B&E 2nd
	"	5.03	72.50	Top
35	0°	4.46	173.07	P. 1. 5th
45	43 1/2	4.84	72.69	2 1/2'
35 1/2	67°	5.62	71.71	5th 2nd
"	"	5.32	72.21	P.C. 40'
58	78°	5.1	72.4	EW-15-58 P.P. 60'
30	90°	5.1	72.4	Prop. 60'
45	127°	4.7	72.8	TB
48	127 1/2	0.2	67.3	BB
66	115°	3.26	73.27	Ch. 12" X 5" 10'