

DIETZEN NO. 384-S

		187.53		5
76	57°	4.2	73.1	T.B.
82	44 1/2	11.1	66.4	B.M.
71	90°	5.0	72.5	
71	79-30	5.34	72.19	T.C.
		5.84	71.72	T.C.
78	65-10	5.34	72.19	T.C.
114	73-12	5.53	72.00	
111	83 1/2	6.16	70.37	T.C.
		5.77	71.76	T.C.
110	89°	5.5	72.0	T.B.
101	107-29	5.9	71.6	T.C.
150	87°	5.0	71.5	T.C.
117	95-10	6.25	71.48	T.C.
		6.43	71.08	T.C.
150	77°	5.0	71.67	T.M.
158	77°	5.1	71.4	T.M.
173	77-40	5.5	72.0	T.C.
171	88-7	5.9	71.6	T.C.
170	36-20	6.34	71.21	T.C.
		5.8	70.73	T.C.
174	82-20	5.5	71.38	T.M.

DIETZEN NO. 384-S

				4
305	37 1/2	12.5	55.8	T.C.
422	40-10	14.9	55.9	T.C.
440	38-10	14.1	56.7	
428	37-2	14.1	56.7	T.C.
419	37	14.1	56.7	T.C.
445	45-2	12.5	55.8	T.C.
470	49 1/2	14.9	55.9	T.C.
T.C. 2. Cl. Case & S. P.L. ext. 1st				
	100°	10.20	167.33	T.C.
52	35°	7.5		
52	1.87	177.53	175.64	
		7.00	168.53	T.C.
150	180°	6.40	71.13	T.C.
160	175°	7.2	70.3	T.C.
157	175-10	6.9	70.6	T.C.
155	167-10	7.3	70.2	T.C.
163	165-50	6.7	70.8	
170	173-10	6.7	70.6	T.C.
115	180°	6.9	71.5	
81	180°	5.68	71.85	
82	165	6.6	70.9	T.P.
83	167°	6.0	71.5	T.C.