Dr. 11A - Bk. 12

OFFICE OF COUNTY ENGINEER
RAMSEY CO. MINN.

Plan Survey

ATLANTIC AVE.

From To

Road Acc't. No.

Date Filed File 11

Plan Survey

Atlantic Avenue

(Or Snail Lake Blvd Extd)

From Hodgson Rd. to Rice St.

Index

Alignment	P. 1-2
Topography	P. 3-7
Cross Sections.	P. 8-13

Alignment

Station	Point
26+30.43	Rice St. (E. Line Sec. 24)
25+79.97	P.O.T.
22+06.62	P.O.T.
7+32.32	P.O.T.
5+32.5	℄ Hodgson = 50+28.6 Beg. Proj.
0+00	


Rice St.
400
400
564
300
300
2632.42
300'
418'
ATLANTIC
HODGSON
120
125
115
600
299'
470'
21
22
20'


784.45
377.65
Hudson Rd
May 1911
astronomical
survey
479.15
141.85


Hub on Tang. Prod.
T.P.
Drilled Hole
Drilled Hole
Stone Mon.
47.12
38.27
1960.08
653.36
2613.44
24' Conc. Hwy.
53.19
74.6
P.P.
P.P.
88°-56'
(40' Sight)
To S.E. Cor. Sec. 24
N.E. Cor. Sec. 24
Fence Line
Hub.
4" Oak
83.72'
6" Oak
53.79
Hub.
E. Co. Rd. "B"
N
W.H.C.
H.W.
J.P.H.
June 5
1935
Hub.
P.P.
32.35
71°-16'
Bolt & Spike
P.P.
73.33
83.13
Face Rd. Sq.
12" Oak.
90°-53'
(60° Sight)
18.54'
Stone Mon.
1331.74'
I.P.
605.51
I.P.
60.
R.R. Spike
665.82
Center Sec. 24
Stone Mon.
6" Oak.
53.45

Topography.

5to.

5

4

3

2

1

0to


Rd. 8'
+71-Guy Wire 16'
+51-Shldr. Rd.
+58-P.P. 15'
+60-Rd. 12'
+14-Shldr. Rd.
Rd-19'
+91-Rd. Sq. 18'
+75-Rd. 10'
+71-P.P. 16'
Hodgson Block
Cultivated
Rd. 8'
+70-Rd. 54'
Road Top
(T.H. #49)
Rd. 18'
+85-Rd. Sq. Slop 20'
+75-Rd. 17'
Rd. 17'
Rd. 9'
+07-P.P. 17'
Rd. 9'
Rd. 17'
+50-F. Cor 38'
Rd. 9'
Timber
(June 5, 1935)
Rd. 17'
Rd. 9'
Rd. 16'
+89-Beg. F. 32'
+35-F. Ent.
Rd. 9'
Rd. 16'

12

11

10

9

8

7

6


+88 Cor. Cult.
Cult.
Cult.
+60 - Cor. Culv. 30'
℄ Rd. 8'
5
℄ Rd. 9'
℄ Rd. 11'
Open Field.
℄ Rd. 12'
℄ Rd. 9'
+14 - Apple Tree 50'
+00 - Ent.
℄ Rd. A
+85 - 10" Bx. El. 33'
+66 - 10" Bx. El. 33'
+45 - 12" Bx. El. 32'
+26 - 10" Bx. El. 32'
+05 - 8" Bx. El. 32'
Rd. 2'
+90 F. Line 36'
Rd. 8'

19

18

17

16

15

14

13


+00 Cor. Timber - 64'
℄ Rd. 5
+94 - 4 small oaks
+82 - 3 10" oaks
Timber 64'
℄ Rd - 8'
℄ Rd. 7'
+00 Cor. cult - 0
℄ Rd. 6
+70 - Cor. Timber
68'
℄ Rd. 6'
+75 - Cor. cult
70
Cultivated.
Cult.
℄ Rd. 4'
℄ Rd. 3
℄ Rd. 8

+42 - E. edge Pave.

+18 - W. edge Pave.

26

25

24

23

22

21

20


+42-E. Paving
Rice St.
24'-Conc. Paving
26711-T.P. 49.5
+18-Pav. Edge
+41-Shoulder Line
10'
+45
Trees
20'
Trees +10
50'
℄ Carlway
65.1
Trees
38'
Carlway X-℄
+60
+40-Int. of Rds.
+43-E X-℄
+38-E Cor. 10'
E-8 Timber Rd
19'
26
2-4" Oaks
Several trees
small oaks
+54-Con. Cult.
31'
Cult.
+37-Cor. Cult.
28'
+33-E Cor
17'
Rd. 22
+92-Con. Cult.
+80-2-6" oak 10'
Cult.
Cult.
958 R.R.
+00 Cor. Cult.
℄ Rd. 11
+10-6 small oaks
℄ Rds. 15

Cross-Sections

Sta.	+	⊼	−	Elev.
B.M.	4.00	928.84		924.84 ✓
3				923.5 ✓
+50				24.1 ✓
4				24.3 ✓
+50				24.2 ✓
5				24.3 ✓
+20				24.2 ✓
+32.5 (Begin Proj)				24.2 ✓
+57				24.0 ✓
+80				24.7 ✓
6				25.3 ✓
T.P.	3.06	931.42 ✓	0.48	928.36 ✓
+65				27.8 ✓

W.H.C.
H.A.W. } 6/6/35
J.A.H.
L.B.H.

9

Lt. ℄ Rt.

R.R. Spike 18" Oak 55' Lt. (Sta. 48+85 Hodgson Rd.)

" " " " 143' Lt. Sta. 5+30

4.9 / 36	4.5 / 25	5.3 / 17	5.0 / 13	5.7 / 9 ←	5.3 / Rd. →	5.8 / 17	5.1 / 20	4.5 / 29	4.7 / 37
4.1 / 40		4.5 / 21	4.0 / 15	5.2 / 11	4.7	5.1 / 16	4.0 / 21	3.6 / 28	3.6 / 40
4.2 / 40		4.1 / 25	4.0 / 13	5.0 / 8	4.5	4.5 / 6 ℄	4.9 / 18	4.1 / 20	3.7 / 35
5.7 / 44	5.5 / 35	5.5 / 20	4.5 / 12	4.9 / 9	4.6	4.6 / 6 ℄	4.7 / 12	5.0 / 18	4.1 / 23	3.5 / 35
Shalt) / Hodg)	5.1 / 50	5.0 / 45	6.1 / 31	5.1 / 24	4.5	4.7 / 13	5.7 / 21	3.6 / 23		3.6 / 50
℄ Hodg =	4.6 / 50				4.6	4.8 / 15	5.5 / 34	7.1 / 42		7.5 / 50
Shldr / Hodg } →	5.0 / 50				4.6 / ℄ Hodg		5.4 / 50	5.6 / 60	- Shldr. Hodg.
3.7 / 60	3.2 / 50	2.7 / 32	5.4 / 26	4.8 / 18	5.1 / 11	4.8	5.1 / 22	4.8 / 50	= ℄ Hodg.
	2.7 / 60	2.5 / 44	1.6 / 30	2.7 / 13	3.9 / 7	4.1	4.8 / 17	5.8 / 56	6.1 / 50	5.8 / 60	- Shldr.
27.0	1.8 / 60		1.5 / 36	1.7 / 14	3.1 / 8	3.5	3.6 / 6	2.2 / 10	2.3 / 29	25.8 3.0 / 60	
27.9	3.5 / 60		3.5 / 25	3.0 / 7	3.6	3.4 / 6	3.8 / 25	27.1 4.3 / 60	

Sta.	+	H.I.	−	Elev.
		931.42 ✓		
7				927.7 ✓
+50				27.6 ✓
8				27.3 ✓
+50				26.5 ✓
9				25.3 ✓
+50				25.0 ✓
10				25.0 ✓
T.P.	5.59	931.28 ✓	5.73	925.69 ✓
+50				25.8 ✓
11				26.0 ✓
+50				26.3 ✓
12				26.9 ✓
+50				27.7 ✓

	Lt.			&	Rt.			
28.0	3.4/60	3.5/30	3.1/7	3.7	3.2/11	3.4/25	3.7/50	3.8/60
27.4	4.0/60	3.8/33	3.5/10	3.8	3.2/14	3.4/30	3.5/50	3.7/60
26.7	4.7/60	4.5/32	4.7/25	4.0/11	4.1	4.0/28		4.1/60
25.9	5.5/60		5.1/25	4.9	4.9/25			4.9/60
25.1	6.3/60		6.4/25	6.1	5.7/25			4.6/60
24.9	6.5/60		6.6/25	6.4	5.9/25			5.2/60
25.4	6.0/60		6.7/25	6.4	6.2/25			6.0/60
26.3	5.0/60		5.5/25	6.0	6.2/13	6.3/25		6.1/60
27.1	4.2/60		4.7/25	5.3	5.7/11	6.0/25		6.5/60
27.8	3.5/60		4.3/25	5.0	5.1/10	6.0/30		6.0/60
27.6	3.7/60		4.0/25	4.4	4.5/13	5.5/30		5.8/60
28.1	3.2/60		3.5/25	3.6	3.7/14	4.7/25		5.0/60

Save Trees.

Tree Line

Ent.

27.6 27.7 27.3 26.5 26.4 26.2 25.4 25.2 24.8 25.3 25.5 26.3

Sta.	+	H. I. 931.28	−	Elev.
13				28.5
+50				29.4
14				29.4
T.P	5.11	935.24	1.15	930.13
+50				29.6
15				29.0
+50				28.8
16				28.7
+50				28.4
B.M.	5.56	935.24	5.56	929.68
17				29.1
+50				30.7
18				32.2
+50				33.0

	Lt.		℄		Rt.	
28.4	2.9 / 60	2.8 / 25	2.8	3.6 / 15	3.9 / 30	4.3 / 60 (27.0)
28.1	3.2 / 60	2.2 / 25	1.9	1.9 / 9	3.0 / 30	3.6 / 60 (27.7)
28.6	2.7 / 60	2.2 / 25	1.9		2.0 / 25	2.4 / 60 (28.9)
27.9	7.3 / 60	6.4 / 25	5.6		5.6 / 25	5.7 / 60 (29.5)
28.1	7.1 / 60	6.6 / 25	6.2		6.3 / 25	5.6 / 60 (29.6)
28.2	7.0 / 60	6.9 / 25	6.4		6.6 / 25	6.2 / 60 (29.0)
28.2	7.0 / 60	7.1 / 25	6.5		6.8 / 25	6.5 / 60 (28.7)
28.4	6.8 / 60	6.8 / 25	6.8		7.2 / 25	7.1 / 60 (28.1)

Sandy Loam

R.R. Spike in 12" Oak 64' Rt Sta 16+72

29.4	5.8 / 60	5.9 / 25	6.4		6.3 / 25	7.1 / 60 (28.1)
31.3	3.9 / 60	4.2 / 25	4.5		5.0 / 25	6.2 / 60 (29.0)
32.2	3.0 / 6.0	3.1 / 25	3.0	3.3 / 10	3.6 / 33	5.2 / 60 (30.0)
32.5	2.7 / 60	2.7 / 25	2.2		3.0 / 25	4.3 / 60 (31.0)

Sta.	+	H.I. 935.24	-	Elev.
19				933.0
T.P.	6.99	939.78	2.45	932.79
+50				33.4
20				33.8
+50				34.5
21				34.6
+50				35.0
22				35.7
T.P.	1.14	937.26	3.66	936.12
+50				34.3
23				32.8
+50				32.5
24				33.9
+50				34.5
T.P.	3.82	937.60	3.48	933.78

	Lt.		℄	Rt.		
32.9	2.3/60	2.4/25	2.2	2.9/16	2.7/35	3.8/60 31.4
33.7	6.1/60	6.4/25	6.4	6.6/14	7.0/25	8.0/60 31.8
34.8	5.0/60	5.6/25	6.0	5.9/10		6.8/60 33.0
35.1	4.7/60	5.1/30	5.3	6.1/25		7.0/60 32.8
35.6	4.2/60	4.7/25	5.2	6.2/28		7.1/60 32.7
36.0	3.8/60	4.3/25	4.8	5.2/19	6.4/30	6.7/60 33.1
37.1	2.7/60	3.4/25	4.1	4.9/18	5.7/33	6.0/60 33.4
34.5	2.8/60	2.7/32	3.0	3.4/23	4.0/50	4.0/60 33.3
33.1	4.2/60	4.4/25	4.5	5.3/25		4.7/60 32.6
33.4	3.9/60	4.3/28	4.8	5.5/25		6.0/60 31.3
34.3	3.0/60	3.0/25	3.4	4.0/25		5.2/60 32.1
34.1	3.1/60	3.3/25	2.8	2.8/25		3.0/60 34.3

Sandy loam

Sta.	+	↗ 937.60 ✓	−	Elev.	
25				33.2 ✓	
+50				33.0 ✓	
+84				32.4 ✓	
T.P.	1.04	925.87 ✓	12.77	924.83 ✓	
26				20.3 ✓	
+06				17.6 ✓	
+13				17.7 ✓	
+18	- W. edge of Conc. Pavement			17.87 ✓	
26+30.43	℄ Rice St.			17.97 ✓	
B.M.	5.82	925.87	5.82	920.05 ✓	
check level T.P.	12.89	937.72	1.04	924.83	
✓	2.02	938.14	1.61	936.11	(G 36.12)
✓	3.88	933.63	8.39	929.75	
B.M.	3.95	933.63	3.95	929.68	
T.P.	3.80	931.28	6.15	927.48	
Int. B.M.			6.47	924.81	(924.84)

	Lt.		℄	Rt.			
32.7	4.9/60	4.8/25	4.4	3.9/21	3.0/45	3.4/60	34.2
32.2	5.4/60	5.0/25	4.6	4.6/25		4.5/60	33.1
31.6	6.0/60	5.4/25	5.2	5.0/25		5.1/60	32.5
	No		5.6	X-Sec.			
15.7	10.2/60	9.0/25	8.3	8.0/25		8.5/60	17.4
26+10 - P.℄ Culv. Drains North.							
16.1	9.8/60	8.9/28	8.2	8.0/25		7.4/60	14.5
16.4	9.51/60.0	9.22/50.0	8.57/25.0	8.00/00	7.56/25.0	7.17/50.0	7.09/60.0 - 18.4
15.3	10.59/100.	9.14/50.0		7.90	7.05/50.0	6.66/100.	19.2

R.R. Spike in T.P. 40'-Rt. Sta. 76+57

Dr 11A Bk 12

Slope Stakes
Atlantic Ave.



Sta. 77+75 to 76+30

Sta	+	∧	−	Grade	
B.M.	7.68	932.52			924.84
5				24.2	
+20				24.2	
+32.5 & Hodgson				24.2	
+57				24.4	
+80				24.5	
6				24.6	
+65				24.8	
7				25.0	
+50				25.2	
8				25.4	
+50				25.6	

Cr Rod | Lt. | ℄ | Rt.

R.R. Spike 18" oak 1 43 Ct. 5+30

8.0	48 / 6.4 +1.6		
7.9	48 / 5.6 +2.3	7.2 +0.7	6.4 +1.5 / 48
7.7	48 / 4.6 +3.1	4.7 +3.0	5.3 +2.4 / 48
7.5	48 / 4.6 +2.9	4.8 +2.7	4.7 +2.8 / 48
7.3	48 / 5.2 +2.1	5.0 +2.3	4.7 +2.6 / 48
7.1	48 / 5.8 +1.3	5.2 +1.9	5.1 +2.0 / 48
6.9	48 / 6.7 +0.2	6.0 +0.9	5.8 +1.1 / 48

Sta.	+	∧	−	Grade	
		932.52			
9				25.8	
+50				26.0	
10				26.2	
+50				26.4	
	7.81	934.25	6.08		976.44
11				26.6	
+50				26.8	
12				27.0	
+50				27.2	
13				27.4	
+50				27.6	
14				27.8	

Cr. Rod	Lt.		Ctr		Rt	
6.7	8.2	48 7.4 / 0.8	7.3 / 18	7.1 / -0.4		5.8 / +0.9 / 48
6.5	8.0	48 / 7.6 / +0.4	7.5 / 18	7.5 / -1.0	7.2 / 18	6.5 / 0.1.6 / 48
6.3	7.8	48 / 7.2 / 0.6	7.5 / 18	7.5 / -1.2	7.0 / 18	7.2 / 0.0.6 / 48
6.1	7.6	48 / 6.2 / 0.4	6.9 / 18	7.3 / -1.2	7.1 / -1.2 / 13.8	7.2 / 0.0.2 / 48
Blue Bp 18' U. Sta. 10+50						
7.7	7.4	48 / 7.4 / +0.3	7.9 / 18	8.3 / -0.6	9.1 / -1.4 / 20.6	9.1 / 0.0.1 / 48
7.5	9.0	48 / 7.0 / +0.5	7.7 / 18	7.8 / -0.3	7.8 / 18	9.0 / 0.0.0 / 48
7.3		48 / 6.5 / +0.8	7.1 / 18	7.4 / -0.1	8.1 / 18	8.3 / 0.0.5 / 48
7.1		48 / 5.4 / +1.2		6.6 / +0.5	7.3 / 18	7.6 / 0.1.0 / 48
6.9		48 / 5.7 / +1.2		5.7 / +1.2		7.3 / 0.1.1 / 48
6.7		48 / 5.6 / +1.1		4.9 / +1.8		6.1 / +0.6 / 48
6.5		48 / 5.7 / +0.8		4.8 / +1.7		5.2 / +1.3 / 48

Sta	+	℄	−	Grade	
		934.25			
14+50				28.0	
15				28.3	
+50				28.6	
16				29.0	
+50				29.43	
	8.68	938.36	4.58		929.68
17				29.8	
+50				30.2	
18				30.7	
+50				31.2	
19				31.7	
+50				32.2	

Cr. Rod	Lt		Ctr		Rt	
6.3						
6.3	48' / 6.0 +0.3		4.6 +1.7		4.7 +1.6	/ 48'
6.0	48' / 6.0 +0.0		5.1 +0.9		4.6 +1.4	/ 48'
5.7 7.2	48' / 6.0 +0.2	x 5.7 18	5.5 +0.2	x 5.5 18	5.9 +0.4	/ 48'
5.3 6.8	48' / 6.1 +0.7	x 6.0 18	5.8 -0.2	x 5.8 18	5.6 +1.2	/ 48'
4.8 6.3	48' / 6.2 +0.1	6.0 18	5.9 -1.1	6.3 -1.5 / 24.0	6.0 +0.3	/ 48'
Spike in 12" Oak .04 Rt. Sta. 16+72						
8.56	48' / 9.1 +1.0		x 9.2 -0.6	x 9.5 18	10.6 +0.0	/ 480'
8.2 9.7	48' / 7.3 +0.9	C.O.6 7.6 18	7.7 +0.5	x 8.2 18	8.9 +0.8	/ 48'
7.7	48' / 6.5 +1.2		6.2 +1.5		7.6 +0.1	/ 48'
7.2	48' / 6.0 +1.2		5.4 +1.8		6.8 +0.4	/ 48'
6.7	48' / 5.6 +1.1		5.0 +1.7		6.4 +0.3	/ 48'
6.2	48' / 4.7 +1.8		5.2 +1.0		6.2 +0.5	/ 48'

Sta	+	∧	−	Grade	
		938.36			
20				32.7	
+50				33.2	
21				33.7	
+50				34.2	
	10.60	940.28	8.68		929.68
22				34.7	
B.M.			3.48		936.80
+75				34.8	
+50				34.6	
+75				34.05	
23				33.20	
+75				32.05	
		938.47			
+50				30.60	



Cr. Rod	Lt.	℄	Rt.
5.7	48' / 3.9 / +1.8	4.8 / +1.2	5.6 / +0.1 / 48'
5.7 (6.7)	48' / 3.5 / +1.7	3.6 / +1.6	5.5 / ℄1.2 / 48'
4.7	48' / 2.7 / +2.0	3.7 / +1.0	5.2 / ℄1.0 / 48'
4.2 (5.7)	48' / 2.3 / +1.9	3.4 / +0.8	5.2 / ℄0.5 / 48'
5.6 (7.1)	48' / 3.3 / +2.3	4.5 / +1.1	6.2 / ℄0.9 / 48'
R.R. Spike Top 8" oak Stump. 53' Lt. 22+00			
5.5		5.3 / +0.2	
5.7 (7.2)	48' / 5.5 / +0.2	5.8 / -0.1	6.8 / ℄0.4 / 48'
6.2 (7.7)	48' / 6.5 / ℄1.2	6.7 / -0.5	7.5 / ℄0.2 / 48'
7.1 (9.1)	48' / 7.0 / +0.1	7.4 / -0.3	7.8 / ℄1.3 / 48'
8.2 (10.2)	48' / 7.6 / +0.6	7.8 / +0.4	8.4 / ℄1.8 / 48
7.8	48' / 5.1 / +2.4	5.9 / +1.9	7.0 / ℄0.8 / 48

Sta.	+	π 988.2	−	Grade.	
23+75				28.8	
24				26.7	
+25				24.6	
+50				22.8	
+75				21.2	
25				19.95	
+25				19.0	
+50				18.3	
+75				17.84	
+84				17.7	
26				17.7	
B.M.					grade

Sr. Rod	Lt.	℄	Rt.
9.6	$\frac{+5.1}{4.8}$	~~$\frac{4.5}{+5.1}$~~	~~$\frac{60}{+6.1}$ 48.4~~
11.7	$60 \mid \frac{4.1}{+7.6}$	$\frac{4.5}{+7.2}$	$\frac{6.2}{+5.5} \mid 60$
~~+5~~			
15.6	$60 \mid \frac{4.7}{+10.9}$	$\frac{3.7}{+11.9}$	$\frac{4.3}{+11.3} \mid 60$
18.4	$60 \mid \frac{5.8}{+12.6}$		$\frac{4.0}{+14.4} \mid 60$
20.1	$60 \mid \frac{6.1}{+14.0}$		$\frac{5.0}{+15.1} \mid 60$
20.7	$60 \mid \frac{6.7}{+14.0}$		$\frac{5.8}{+14.9} \mid 60$

40' Rt. Sta. 76+57 Spk in T.P.

9-17-97 CPW

Sta.	+	Δ	−	Grade.