

Office of Survey Co. Engineer

ST. PAUL, MINN.

Cleveland Ave.

File No. "3" 23-05

---

ENGINEERS'  
FIELD BOOK  
No. 10-08

---

# EUGENE DIETZGEN CO.

DRAWING MATERIALS, MATHEMATICAL and  
SURVEYING INSTRUMENTS

Chicago New York San Francisco New Orleans Pittsburg Toronto

Distances from Center of Roadway for Cross-Sectioning  
Roadway 16 feet wide. Side Slopes 1 on 1.  
For Single Track Embankment.


H	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	H
0	8.0	8.1	8.2	8.3	8.4	8.5	8.6	8.7	8.8	8.9	0
1	9.0	9.1	9.2	9.3	9.4	9.5	9.6	9.7	9.8	9.9	1
2	10.0	10.1	10.2	10.3	10.4	10.5	10.6	10.7	10.8	10.9	2
3	11.0	11.1	11.2	11.3	11.4	11.5	11.6	11.7	11.8	11.9	3
4	12.0	12.1	12.2	12.3	12.4	12.5	12.6	12.7	12.8	12.9	4
5	13.0	13.1	13.2	13.3	13.4	13.5	13.6	13.7	13.8	13.9	5
6	14.0	14.1	14.2	14.3	14.4	14.5	14.6	14.7	14.8	14.9	6
7	15.0	15.1	15.2	15.3	15.4	15.5	15.6	15.7	15.8	15.9	7
8	16.0	16.1	16.2	16.3	16.4	16.5	16.6	16.7	16.8	16.9	8
9	17.0	17.1	17.2	17.3	17.4	17.5	17.6	17.7	17.8	17.9	9
10	18.0	18.1	18.2	18.3	18.4	18.5	18.6	18.7	18.8	18.9	10
11	19.0	19.1	19.2	19.3	19.4	19.5	19.6	19.7	19.8	19.9	11
12	20.0	20.1	20.2	20.3	20.4	20.5	20.6	20.7	20.8	20.9	12
13	21.0	21.1	21.2	21.3	21.4	21.5	21.6	21.7	21.8	21.9	13
14	22.0	22.1	22.2	22.3	22.4	22.5	22.6	22.7	22.8	22.9	14
15	23.0	23.1	23.2	23.3	23.4	23.5	23.6	23.7	23.8	23.9	15
16	24.0	24.1	24.2	24.3	24.4	24.5	24.6	24.7	24.8	24.9	16
17	25.0	25.1	25.2	25.3	25.4	25.5	25.6	25.7	25.8	25.9	17
18	26.0	26.1	26.2	26.3	26.4	26.5	26.6	26.7	26.8	26.9	18
19	27.0	27.1	27.2	27.3	27.4	27.5	27.6	27.7	27.8	27.9	19
20	28.0	28.1	28.2	28.3	28.4	28.5	28.6	28.7	28.8	28.9	20
21	29.0	29.1	29.2	29.3	29.4	29.5	29.6	29.7	29.8	29.9	21
22	30.0	30.1	30.2	30.3	30.4	30.5	30.6	30.7	30.8	30.9	22
23	31.0	31.1	31.2	31.3	31.4	31.5	31.6	31.7	31.8	31.9	23
24	32.0	32.1	32.2	32.3	32.4	32.5	32.6	32.7	32.8	32.9	24
25	33.0	33.1	33.2	33.3	33.4	33.5	33.6	33.7	33.8	33.9	25
26	34.0	34.1	34.2	34.3	34.4	34.5	34.6	34.7	34.8	34.9	26
27	35.0	35.1	35.2	35.3	35.4	35.5	35.6	35.7	35.8	35.9	27
28	36.0	36.1	36.2	36.3	36.4	36.5	36.6	36.7	36.8	36.9	28
29	37.0	37.1	37.2	37.3	37.4	37.5	37.6	37.7	37.8	37.9	29
30	38.0	38.1	38.2	38.3	38.4	38.5	38.6	38.7	38.8	38.9	30
31	39.0	39.1	39.2	39.3	39.4	39.5	39.6	39.7	39.8	39.9	31
32	40.0	40.1	40.2	40.3	40.4	40.5	40.6	40.7	40.8	40.9	32
33	41.0	41.1	41.2	41.3	41.4	41.5	41.6	41.7	41.8	41.9	33
34	42.0	42.1	42.2	42.3	42.4	42.5	42.6	42.7	42.8	42.9	34
35	43.0	43.1	43.2	43.3	43.4	43.5	43.6	43.7	43.8	43.9	35
36	44.0	44.1	44.2	44.3	44.4	44.5	44.6	44.7	44.8	44.9	36
37	45.0	45.1	45.2	45.3	45.4	45.5	45.6	45.7	45.8	45.9	37
38	46.0	46.1	46.2	46.3	46.4	46.5	46.6	46.7	46.8	46.9	38
39	47.0	47.1	47.2	47.3	47.4	47.5	47.6	47.7	47.8	47.9	39
40	48.0	48.1	48.2	48.3	48.4	48.5	48.6	48.7	48.8	48.9	40


Example—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 30.6. For same slopes but other widths of roadbed, correct above figures by one-half difference in width of roadbed; thus in example above, for 20 ft. roadbed distance will be  $30.6 + (20 - 16) \div 2$  or 2 ft. added to  $30.6 = 32.6$ . For slopes of 1 on  $1\frac{1}{2}$  see inside of back cover.

Copyright, 1914, by Eugene Dietzgen Co.

# Index -

Page to Page -		Description	Sta. to Sta.	
3	5	Cross Sections ✓ (23-05)	0	13
6	8	Grade Stakes (23-05)	0	13
9	11	Pavement Stakes (23-04)	0	13
13	14	Final Cross-Sec. (23-05)	0	13
68	69	Final Cross-Sec. Borrow Pit ✓ (23-05)	0	-3
73	74	Cross-Sec. Borrow Pit ✓ (23-05)	0	-3
63	65	Cross Sec. - (23-62)	19	26





Proj # 23-05

X Sections & Slope stakes from Sta. 0+00  
to Sta. 13+00.

Sta	+	H.I.	-	Elev	Grade
B.M.	2.43	303.05		300.62	
0+00			2.9	300.2	297.9
1			5.5	297.6	297.5
+74			7.4	295.5	
	1.17	298.55	5.67	297.38	
2			3.7	297.9	295.1
+50			4.7	293.9	
3			5.7	292.9	292.7
T.P.	3.44	295.79	4.20	292.35	
+22			3.4	292.4	
+42			3.7	292.1	
4			4.4	291.4	290.3
5			6.7	287.1	287.9
T.P.	2.77	288.64	9.93	285.74	
B.M.			5.57	283.07	
6			2.4	286.0	285.7

Lt.

Rt.

7/13/23

C. 1900  
S. Simmons  
W. 1/2  
S. 1/2

SpK. in Tel. pole 25' Lt of Sta. 6 + 15

0.18	+11.8	2.0	3.2	3.1	2.9	0.0.2
36.8	33	17	11	18	38	25.2

0.23	3.2	3.7	6.9	5.9	4.7	6.1	6.2	F. 0.8
122	33	23	14	10	25	29	33	29.2
4.2	6.1	8.8	2.7	2.7	8.0	9.2	11.6	8.0
33	20	14	7	4	27	22	27	33

F. 1.0	4.1	5.4	3.7	4.0	6.4	7.0	F. 2.9
27.8	33	17	9	13	18	33	22.3
13.1	16.7	4.2	5.1	5.2	10.5	11.1	
33	22	9	4	17	27	33	

F. 8.7	-8.4	6.1	5.6	5.8	6.9	5.7	-9.6	F. 7.8
32.0	33	12	8	6	6	11	33	33.7

7/14/23

-15.8	3.4	3.6	3.5	3.6	-13.0
33	10	6	3	12	33
-12.5	3.9	2.8	3.9	-12.3	
33	11	7	10	33	

F. 10.8	-9.9	4.6	4.3	4.4	6.1	-12.5	-16.3	F. 16.4
36.2	33	11	7	11	14	33	40	47.4

F. 8.1	-8.3	-2.9	2.0	6.5	4.8	6.7	-12.1	F. 14.0
36.3	33	25	10	8	4	11	33	41.9

Nail in Tel. pole 25' Lt Sta. 6 + 69

F. 15.5	7.5	7.4	3.0	2.6	2.7	9.4	10.2	10.4	F. 9.4
42.2	33	20	11	9	11	24	28	33	30.1

Proj # 23-05

Continued

Sta	+	H.I.	-	Elev	Grade
		288.67			
7			9.4	284.2	284.5
8			5.0	283.6	283.9
9			4.7	283.9	283.9
I.P.	6.02	290.41	4.25	284.39	
10			6.0	284.4	284.3
11			5.5	284.9	284.7
12			4.7	285.5	285.3
+80			3.4	286.8	286.8
13					286.9
B.M.			2.74	287.67	
+073					

See page 14 for Original X Sec.

Lt

Rt 2/14/23

F.24	6.1	6.9	6.8	4.5	4.6	4.7	4.6	8.0	8.9	8.9	F.A.C
24.6	33	29	18	10	9	7	12	19	26	33	24.9

F.1.7	6.2	6.5	5.2	5.4	5.0	5.5	7.3	7.5	F.2.6
20.7	35	17	12	6	9	12	17	38	21.9

F.1.6	6.0	6.3	6.9	4.7	4.9	4.9	6.3	6.7	F.1.9
13.4	33	21	19	11	9	12	18	33	23.1


F.1.3	7.2	7.3	8.3	7.7	6.1	6.1	5.9	6.2	6.7	7.8	7.9	F.1.8
23.7	38	22	21	18	12	8	5	10	13	19	33	23.2


F.0.8	6.3	6.4	7.0	5.5	5.5	5.8	6.0	6.7	7.2	F.1.3
14.2	33	33	20	10	9	5	14	16	33	26.7

0.9.6	4.1	4.3	5.4	5.1	5.9	4.9	5.0	5.4	5.1	5.1	6.0
23.0	33	21	19	16	14	10	9	10	15	33	33

2.8	3.6	5.1	5.2	3.9	4.0	3.7	4.4	4.1	F.0.8
23	19	18	19	16	9	5	16	33	24.2
2.9		0.0.7							
33		25.7							

Top of Mont. 13+17.3





8/2/23

Grade stakes sta 00 to 13

23±05

Sta	+	M.I	-	Elev	Grade
B.M.	0.72	301.34			300.62
0+00			1.1	300.2	99.9
1			3.8	297.5	97.5
2			6.6	294.7	95.1
3			8.5	292.8	92.7
4			11.0	290.3	90.3
T.P.	2.12	292.42	11.04	290.30	
5			4.6	87.8	87.9
6			6.6	85.8	85.9
B.M.	9.35	292.39	9.35	283.07	283.04
7			7.9	84.5	84.5
8			8.5	83.9	83.9
9			8.4	84.0	83.9
T.P.	6.03	289.91	8.51	283.88	
10			5.6	84.3	84.3
11			5.1	84.8	84.7

Fair - cool

Carley - Transit 7  
Persons - Level - Rod  
Eck - Head-chain  
Briggs - Rear-chain

R.R. spike in tele pole Rt. of sta 0+15

Spike in tele pole Lt. of sta 6+69

Sta		H.I		Elev.	Grade
		289.91			
11 +50			4.6	85.3	84.9
12			4.4	85.5	85.3
	450		3.9	86.0	86.25
13					86.9
	B.M.		2.30	287.61	287.60

Top of monument on Leventeur + Cleveland.

8/9/23

## Pavement - stakes.

Sta	r	H.I	-	Elev	Sub Grade
BM	2.92	303.54		300.62	
0 +00					299.90 ✓
+25					99.30 ✓
+50					98.70 ✓
+75					98.10 ✓
1					97.50 ✓
+25					96.90 ✓
+50					96.30 ✓
+75					95.70 ✓
2					95.10 ✓
+25					94.50 ✓
+50					93.90 ✓
+75					93.30 ✓
3					92.70 ✓
+25					92.10 ✓
+50					91.50 ✓
+75					90.90 ✓
TP	0.72	292.24	12.02	291.52	
4					90.30 ✓
+25					89.70 ✓
+50					89.10 ✓
+75					88.50 ✓

Pavement  
Grade

R.R. spike in tele pole R of sta 0+15

300.525 ✓

99.925 ✓

99.325 ✓

98.725 ✓

98.125 ✓

97.525 ✓

96.925 ✓

96.325 ✓

95.725 ✓

95.125 ✓

94.525 ✓

93.925 ✓

93.325 ✓

92.725 ✓

92.125 BMidge

91.525 ✓

90.925 ✓

90.325 ✓

89.725 ✓

89.125 ✓

Sta	+	H.I.	-	Elev	Sub Grade
	0.72	292.24			
5 ✓					287.90 ✓
+25					287.355 ✓
+50					286.779 ✓
+75					286.204 ✓
6					285.90 ✓
+25					285.450 ✓
+50					285.080 ✓
+75					284.740 ✓
B.M.	6.47	289.51	9.20	283.04	✓
7					284.501 ✓
+25					84.301 ✓
+50					84.08 ✓
+75					83.920 ✓
8					83.901 ✓
+25					83.703 ✓
+50					83.779 ✓
+75					283.850 ✓
9 ✓					283.901 ✓
+25					84.001 ✓
+50					84.121 ✓
+75					84.201 ✓

aving.  
Grade.

88.525 ✓

87.980 ✓

87.404 ✓

86.829 ✓

86.525 ✓

86.075 ✓

85.705 ✓

85.365 ✓

R.R. spike in tele pole L of sta 4769

85.126 ✓

84.926 ✓

84.705 ✓

84.545 ✓

84.526 ✓

84.328 ✓

84.404 ✓

84.475 ✓

84.526 ✓

84.626 ✓

84.726 ✓

84.826 ✓

Sta	+	H.I.	-	Elev	Sub Grade
	6.47	289.51			
10					84.30 ✓
	+25				84.40 ✓
	+50				84.50 ✓
	+75				84.60 ✓
11					84.70 ✓
	+25				84.80 ✓
	+50 ✓				84.90 ✓
	+75				85.02 ✓
12					85.30 ✓
	+25				85.778 ✓
	+50 ✓				86.25 ✓
	+80				86.88 ✓
B.M.			1.85	287.66	287.60

Pavement  
Grade

84.925 ✓

85.025 ✓

85.125 ✓

85.225 ✓

85.325 ✓

85.425 ✓

85.525 ✓

85.727 ✓


85.925 ✓


86.403 ✓

86.875 ✓

87.505

Top of monument Harper Ave.





Proj. # 23-05

Final X Sections from  
Sta. 0+00 to End of Proj.

Sta.	+	H.I.	-	Elev.
B.M.	1.77	302.39 ✓		300.62
0+00			2.1	300.3
1			4.9	297.5
+74			4.8	295.6
2			7.2	295.2 ✓
T.P.	5.59	297.99 ✓	10.04	292.35 ✓
+50			9.0	93.9
3			5.4	92.5
+22			6.1	91.8
+42			6.1	91.8
4			7.7	90.2
5			9.9	88.0
T.P.	2.92	289.47 ✓	11.39	286.55 ✓

Lt.

Rt.

8/13/23

S.P.K. in 70' over R. Sta. 0+15

<u>513.37</u>	<u>1.9</u>	<u>8.0</u>	<u>5.3</u>	<u>3.4</u>	<u>1.8</u>	<u>2.3</u>	<u>3.4</u>	<u>2.2</u>	<u>2.2</u>
38	34	35	20	14	14	22	37	33	

<u>2.6</u>	<u>2.0</u>	<u>7.0</u>	<u>7.0</u>	<u>5.0</u>	<u>5.0</u>	<u>6.1</u>	<u>6.2</u>	<u>5.6</u>	<u>5.5</u>
33	30	23	20	16	16	19	14	24	33

<u>4.2</u>	<u>4.1</u>	<u>8.5</u>	<u>8.8</u>	<u>6.9</u>	<u>6.8</u>	<u>7.0</u>	<u>7.0</u>	<u>6.6</u>	<u>7.9</u>	<u>8.7</u>	<u>7.4</u>	<u>7.6</u>
33	26	22	19	16	14	13	12	14	17	21	39	32

<u>8.1</u>	<u>5.6</u>	<u>9.4</u>	<u>9.4</u>	<u>7.4</u>	<u>7.2</u>	<u>7.5</u>	<u>7.6</u>	<u>7.7</u>	<u>10.7</u>	<u>10.9</u>	<u>11.0</u>
33	25	23	20	14	13	12	14	21	24	28	33

Top of Wall on bridge at the S. E. Cor.

<u>123</u>	<u>12.2</u>	<u>2.6</u>	<u>7.1</u>	<u>4.1</u>	<u>3.7</u>	<u>9.7</u>	<u>11.4</u>
33	31	14	12	13	16	27	33

288.44

5.0

288.02

<u>6.4</u>	<u>4.0</u>	<u>4.7</u>	<u>5.3</u>	<u>5.3</u>	<u>4.1</u>	<u>4.2</u>	<u>5.0</u>	<u>5.0</u>
34	15	14	12	13	15	17	33	33.7

288.44

5.5

288.02

<u>8.5</u>	<u>7.8</u>	<u>5.6</u>	<u>5.8</u>	<u>6.1</u>	<u>6.2</u>	<u>8.6</u>
33	32.5	15	12	12	14	33

288.44

6.8

288.02

<u>7.9</u>	<u>8.6</u>	<u>4.8</u>	<u>6.5</u>	<u>6.1</u>	<u>7.4</u>
33	30	29	13	12	37

288.44

6.5

288.02

<u>2.4</u>	<u>7.0</u>	<u>7.2</u>	<u>7.7</u>	<u>7.9</u>	<u>13.1</u>
34	18	15	12	20	43

288.44

8.8

288.02

<u>8.8</u>	<u>8.7</u>	<u>9.3</u>	<u>9.5</u>	<u>10.6</u>	<u>10.3</u>	<u>13.5</u>	<u>14.3</u>
33	31.3	18	14	13	18	37.4	41.0

Sta.	+	H.I.	-	Elev.
		289.47		
6			3.4	85.9
B.M.			6.42	283.05 ✓
7			4.9	84.6
8			5.5	84.0
9			5.5	84.0
T.P.	5.90	290.39 ✓	4.78	284.49 ✓
10			5.9	84.5
11			5.4	85.0
12			4.9	85.5
+80			3.5	86.9
13			2.9	87.5
+07.3	Edge of pavement		2.79	87.60
B.M.			2.73	287.04 ✓

L

R

8/16/23

(3.5)

$\frac{8.4}{33}$   $\frac{8.7}{28}$   $\frac{2.8}{17}$   $\frac{3.8}{14}$   $\frac{3.7}{12}$   $\frac{3.7}{12}$   $\frac{2.4}{16}$   $\frac{5.4}{20}$   $\frac{10.9}{30}$   $\frac{10.9}{33}$

Nail in Talpole L. Sta. 6+69

$\frac{6.9}{33}$   $\frac{7.5}{25}$   $\frac{3.8}{14}$   $\frac{5.0}{12}$   $\frac{5.3}{12}$   $\frac{4.9}{12}$   $\frac{4.6}{13}$   $\frac{4.3}{17}$   $\frac{9.6}{28}$   $\frac{9.7}{33}$

(5.9)

$\frac{7.2}{33}$   $\frac{7.6}{22}$   $\frac{7.2}{20.5}$   $\frac{4.8}{15}$   $\frac{5.5}{12}$   $\frac{5.7}{12}$   $\frac{6.0}{19}$   $\frac{8.1}{22}$   $\frac{8.4}{33}$

(5.6)

$\frac{6.8}{33}$   $\frac{7.1}{22}$   $\frac{4.3}{14}$   $\frac{5.0}{12}$   $\frac{5.6}{12}$   $\frac{5.2}{17}$   $\frac{7.7}{22.3}$   $\frac{7.3}{33}$

(6.0)

$\frac{7.2}{33}$   $\frac{7.2}{20.6}$   $\frac{5.5}{17}$   $\frac{6.0}{12}$   $\frac{6.2}{12}$   $\frac{5.4}{19}$   $\frac{7.8}{23.0}$   $\frac{7.7}{33}$

(5.5)

$\frac{6.3}{33}$   $\frac{6.4}{24}$   $\frac{7.4}{25}$   $\frac{7.5}{20.7}$   $\frac{5.4}{16}$   $\frac{5.5}{12}$   $\frac{5.9}{12}$   $\frac{5.2}{15}$   $\frac{5.1}{20}$   $\frac{6.9}{24.8}$   $\frac{7.2}{33}$

(4.9)

$\frac{4.1}{33}$   $\frac{4.5}{26}$   $\frac{5.9}{24}$   $\frac{5.5}{20.2}$   $\frac{4.5}{16}$   $\frac{4.7}{12}$   $\frac{5.1}{12}$   $\frac{4.6}{17}$   $\frac{5.8}{20}$   $\frac{6.0}{25}$   $\frac{5.0}{24}$   $\frac{5.1}{33}$

(3.6)

$\frac{2.9}{33}$   $\frac{1.8}{26}$   $\frac{4.4}{24}$   $\frac{4.7}{19}$   $\frac{3.2}{14}$   $\frac{3.4}{12}$   $\frac{3.7}{12}$   $\frac{4.0}{17}$   $\frac{5.2}{24}$   $\frac{4.2}{25}$   $\frac{4.2}{33}$

(2.9)

Original X Sec.


$\frac{2.7}{33}$   $\frac{2.0}{12}$   $\frac{3.0}{12}$   $\frac{3.8}{33}$


(2.8)

Original X Sec.

$\frac{2.54}{33}$   $\frac{3.39}{33}$

Top of Mount, 13+73





Proj. # 23-02

L.A. 2024

Pavement stakes from  
Sta. 0+00 to Sta.

Sta.	+	H.I.	-	Elev.	Sub Grade
B.M.				244.2	
0+00					263.20
+25					262.90
+50					262.60
+75					262.30
1+00					262.00
+25					261.70
+50					261.40
+75					261.10
2+00					260.80
+25					260.50
+50					260.20
+75					259.92
3+00					259.67
+25					259.47
+50					259.30
+75					259.15

8/10/23

Paye.  
Grade

Nail in 20" Box S.W. Cor. Small - Larp

263.825

263.525

243.225

262.925

262.625

262.325

262.025

261.725

261.425

261.125

260.825

260.525

260.225

260.075

259.925

259.775

Sta.	+	M.I.	-	Elev.	Sub. Grade
4+00					259.0
+25					258.84
+50					258.73
+75					258.62
5+00					258.52
+25					258.45
+50					258.38
+75					258.33
6+00					258.30

2/16/23

Pay  
Order

259,625

259,485

259,355

259,245


259,145


259,075

259,005

258,955

258,925





Larp. Ave. Proj. # 23-62

X. Sections & Slope stakes  
from Sta 19+00 to Sta. 26+55.5

Sta.	+	H.I.	-	Elev.	Grade
B.M.	3.54	262.71		259.15	
T.P.	3.22	257.99	7.94	254.77	
19			3.7	254.3	254.1
20			4.7	253.3	253.4
21			5.0	253.0	253.3
22			4.8	253.2	253.1
23			4.8	253.2	252.8
24			5.4	252.7	252.5
T.P.	4.54	250.90	5.43	252.54	

L+

RT 7/23/23

Crane  
Simmons  
Walsh  
Kilberg

Wall 1A 12' ... R, Sta. 1+ + 25.

G. Rod  
C.B.F.

1.9 F0.8 4.7 3.9 3.7 4.7 4.2 4.4 4.9 3.6 3.0 2.8 3.6 C.04  
C.02 20.3 33 24 21 17 11 14 19 24 33 31.2

4.4 F1+5.8 5.4 5.4 4.7 6.0 6.0 5.2 5.2 5.0 6.0 5.3 4.4 4.5 3.2 F0.8  
C.03 20 30 30 25 21 20 17 9 12 14 20 24 23 20.2

4.7 F1.5 6.2 5.1 5.0 5.5 6.2 5.5 5.0 5.2 6.2 5.4 4.9 5.4 5.1 5.3 F0.6  
C.05 20 33 28 24 21 17 6 10 15 19 27 27 30 20.4

4.9 F1.3 6.2 5.1 4.7 5.1 6.2 5.6 5.3 5.5 6.0 6.1 5.2 5.2 5.4 F.0.5  
C.01 20 33 27 24 21 19 15 10 15 18 22 33 21.4

5.2 F0.9 6.1 5.0 4.7 5.1 6.1 5.3 5.3 6.8 6.1 4.4 4.5 5.2 0.0  
C.04 20.1 33 27 23 20 19 9 16 18 25 33 21

5.5 5.7 5.7 5.1 5.4 5.6 6.4 5.9 5.6 5.7 6.0 6.8 6.8 6.0 5.2 4.2 4.3 5.4 0.0  
C.01 33 31 29 24 22 20 15 7 8 12 14 15 17 25 28 33 24.1  
4.4 F.0.9  
20.1

Proj' # 23-62

Continued

Sta.	+	H.I.	-	Elev	Grade
		156.90			
25			4.4	252.5	252.5
24			4.3	252.6	252.0
	+34		4.4	252.5	
	+39		4.4	252.5	
	+51.5	End of Proj.	4.4	252.5	
	+55.5	☿ of Hamline Ave	4.4	252.5	
B.M.			4.30	252.60	252.63
B.M.			3.54	253.34	

S. Rod  
C.B.F.

at

ft.

7/23/23

A.C	F <sup>10</sup> 5.8	5.0	4.7	4.8	5.1	5.3	4.8	4.3	4.2	5.3	6.2	5.7	4.9	4.3	4.4	5.4	F01
G.02	20	33	28	23	20	17	13	4	4	7	14	17	25	30	30	26.2	

A.7	F07	5.6	5.0	4.6	5.8	5.3	4.3	4.6	5.4	6.0	5.1	4.4	4.9	5.3	F04
G.06		22	33	24	20	17	5	4	11	13	24	27	33	26.6	

5.3	4.9	5.2	4.5	4.9	5.7	5.5
33	28	32	11	19	24	33


5.7	4.5	4.7	4.8
33	13	24	33


4.3	4.0	4.4
33	13	35

3.6	4.4	4.6	4.5	4.5	4.9
100	30	14	11	33	100

Nail in 18" oak, ft. STN 24 + 45

Splk in Tel. pole 54' Lt of STN 26 + 95





Cleveland

Proj # 23-05

Final X Sections for borrow pit  
from Sta. 0+00 to Sta. -3+00

Station	+	H.I.	-	Elev.
B.M.	12.83	313.45	4	300.62
-3+00			8.1	
-2+87			8.3	
-2+75			8.4	
-2+50			9.0	
-2+25			9.3	
-2+00			9.5	
-1+75			9.7	
-1+65			9.7	
-1+50			10.2	
-1+40			10.4	
I.P.	12.02	325.32	0.15	313.30 ✓
-1+25	The same as original X section			

8/13/23

Wye Level

Right

S.P.A. in 70' interval of 529.0115

7.5	6.7	7.0
30	72	130

325.32 H.I.

7.0	7.1	6.3	6.7	9.0
28	72	83	147	161

325.32

7.3	6.3	6.2	6.3	8.2
30	70	78	144	159

325.32

5.6	5.6	7.1	6.4	5.5	5.1	6.0	2.3	8.1
10	21	25	43	100	107	143	151	155

325.32

9.0	6.1	6.0	7.5	4.6	2.4	4.5	5.9	5.9	1.2	7.8
14	25	46	55	86	100	117	123	142	150	159

325.32

7.0	4.9	8.2	6.8	4.7	7.8	4.1	5.8	4.3	6.1	6.1	2.0	2.2
10	24	30	38	56	60	92	100	109	115	142	148	152

325.32

9.7	5.9	8.7	7.9	6.4	4.1	4.5	6.5	6.7	1.7	7.8
7	27	33	70	94	99	108	112	139	147	151

325.32

9.6	7.2	7.9	3.8	8.4	6.4	6.5	2.8	6.6
4	65	76	105	117	129	142	148	151

325.32

10.6	8.2	7.6	4.0	8.6	7.9	3.7	7.0	6.4	2.5	5.7	5.6
2.0	48	52	65	75	100	104	112	138	142	147	150

325.32

10.1	5.0	8.5	5.7	3.1	12.7	6.0	5.2	4.9
36	60	75	74	100	121	132	133	150

138

## Cleveland

Continued

Sta.	+	H.I.	-	Elev.
-1+00			±	
				The same as Original 1.500
-90			"	"
-75			"	"
-63			"	"
B.M.	10.00	311.22 ✓		300.02
-50			9.9.	
-35			10.2	
-25			10.4.	
0+00			✓ 10.9.	
T.P.	7.41	314.54	2.29	308.93 ✓

2

Sp. in Tol. Lake R. 549. 0+15

<u>100</u>	<u>7.5</u>	<u>6.8</u>	<u>1.9</u>
17	30	39	84

Same as Original X Sec.

<u>10.3</u>	<u>12.0</u>	<u>12.0</u>	<u>10.1</u>	<u>10.3</u>	<u>8.7</u>	<u>8.2</u>	<u>5.6</u>	<u>4.0</u>
17	20	22	26	29	45	62	68	80

~~316.54~~

<u>11.2</u>	<u>12.2</u>	<u>11.9</u>	<u>2.9</u>
15	20	24	38

1.7 1.8

44 59


Same as C. X. Sec.

~~316.54~~

<u>10.7</u>	<u>12.4</u>	<u>12.1</u>	<u>9.4</u>
16	19	25	32

<u>4.6</u>	<u>5.3</u>
38	45

same as C. X. Sec.



The image shows a page of graph paper with a grid of small squares. A vertical red line is drawn on the left side, creating a margin. The grid covers most of the page, leaving a small blank area at the bottom. The paper is aged and yellowed.

Cleveland Proj. 23-05

Base  
LineX. Sections for borrow pit from  
Sta. 0+00 to Sta. - 3+00

Sta.	+	H.I.	-	Elev
0+00	7.75	300.37		300.62
-25			7.4	300.8
-35			7.2	301.2
-50			7.0	301.4
-63			6.8	301.6
-75			6.5	301.9
-90			6.3	302.1
-1+00			6.2	302.2
-1+25			5.7	302.7
-1+40			5.4	303.0
-1+50			5.2	303.2

Original X sections

7/13/23

Hand Level

Right

SPL. IN TEL. pole 25' Sta. 0+15

$$+ \frac{10.3}{17} + \frac{11.5}{32} + \frac{10.8}{45} + \frac{9.8}{85} + \frac{9.4}{137} + \frac{9.4}{150}$$

$$+ \frac{1.3}{18} + \frac{12.5}{33} + \frac{14.7}{39} + \frac{13.9}{59} + \frac{10.9}{62} + \frac{8.3}{87} + \frac{12.4}{101} + \frac{10.9}{118} + \frac{9.9}{150}$$

$$- \frac{0.7}{13} + \frac{2.3}{26} + \frac{11.0}{61} + \frac{4.6}{68} + \frac{5.6}{80} + \frac{9.3}{94} + \frac{14.0}{127} + \frac{10.7}{140} + \frac{9.9}{150}$$

$$\frac{0.0}{16} + \frac{3.0}{34} + \frac{8.0}{82} + \frac{11.2}{106} + \frac{17.3}{114} + \frac{12.5}{150}$$

$$\frac{0.0}{19} + \frac{5.1}{30} + \frac{4.2}{37} + \frac{8.3}{68} + \frac{6.3}{79} + \frac{10.9}{91} + \frac{13.6}{121} + \frac{19.4}{152} + \frac{14.3}{156}$$

$$- \frac{0.2}{13} + \frac{4.0}{26} + \frac{3.3}{39} + \frac{2.2}{44} + \frac{9.4}{87} + \frac{11.1}{121} + \frac{18.7}{128} + \frac{10.7}{150}$$

$$+ \frac{0.9}{44} + \frac{4.6}{57} + \frac{6.8}{80} + \frac{9.3}{99} + \frac{12.9}{115} + \frac{18.7}{121} + \frac{15.7}{150}$$

$$+ \frac{1.7}{40} + \frac{3.0}{56} + \frac{5.4}{69} + \frac{5.3}{82} + \frac{5.0}{90} + \frac{8.7}{102} + \frac{12.3}{118} + \frac{19.8}{130} + \frac{17.3}{150}$$

$$+ \frac{2.0}{38} + \frac{4.7}{83} + \frac{9.0}{112} + \frac{12.2}{124} + \frac{14.7}{127} + \frac{17.9}{135} + \frac{16.9}{150}$$

$$+ \frac{0.3}{36} + \frac{5.7}{64} + \frac{2.0}{78} + \frac{3.6}{95} + \frac{6.8}{103} + \frac{9.6}{121} + \frac{13.6}{130} + \frac{18.1}{137} + \frac{14.0}{150}$$

$$+ \frac{0.7}{19} + \frac{1.6}{48} + \frac{5.6}{59} + \frac{5.7}{66} + \frac{1.5}{95} + \frac{2.1}{94} + \frac{7.3}{105} + \frac{10.9}{122} + \frac{17.9}{133} + \frac{16.2}{150}$$

## Cleveland

Continued

Stn.	+	H.I.	-	Elev.
		308.37		
-1+65			4.9	303.5 ✓
-1+75			4.7	303.7 ✓
-2+00			4.5	303.9 ✓
-2+25			4.3	304.1 ✓
-2+50			3.9	304.5 ✓
-2+75			3.5	304.9 ✓
-2+87			3.3	305.1 ✓
-3+00			3.1	305.3 ✓

9/13/53

4

$$+\frac{2.0}{66} + \frac{1.1}{95} + \frac{5.4}{115} + \frac{11.0}{120} + \frac{17.2}{133} + \frac{15.2}{150}$$

$$+\frac{2.9}{23} + \frac{0.3}{32} + \frac{2.8}{68} + \frac{2.5}{98} + \frac{6.4}{109} + \frac{17.0}{127} + \frac{14.8}{146} + \frac{15.2}{150}$$

$$+\frac{0.4}{11} + \frac{4.4}{24} + \frac{1.7}{30} + \frac{2.8}{38} + \frac{1.8}{68} + \frac{3.2}{92} + \frac{6.3}{104} + \frac{15.7}{119} + \frac{13.1}{142} + \frac{13.1}{150}$$


$$+\frac{3.2}{24} + \frac{3.1}{46} + \frac{1.8}{56} + \frac{3.0}{76} + \frac{4.6}{95} + \frac{14.1}{109} + \frac{12.4}{142} + \frac{13.0}{150}$$


$$+\frac{0.6}{10} + \frac{3.0}{20} + \frac{2.1}{26} + \frac{3.1}{68} + \frac{12.8}{83} + \frac{11.2}{88} + \frac{12.7}{150}$$

$$+\frac{1.3}{16} + \frac{2.6}{43} + \frac{2.8}{50} + \frac{3.3}{53} + \frac{8.2}{60} + \frac{8.6}{86} + \frac{10.6}{103} + \frac{11.3}{120} + \frac{11.8}{137} + \frac{12.5}{150}$$

$$+\frac{0.8}{11} + \frac{1.9}{35} + \frac{4.8}{53} + \frac{8.2}{61} + \frac{8.3}{67} + \frac{8.5}{87} + \frac{10.2}{90} + \frac{10.8}{124} + \frac{11.0}{158}$$

$$+\frac{2.0}{35} \quad +\frac{2.0}{125} = \quad +\frac{2.0}{150}$$





10

30

22.0  
22  
22

7.28

7.78

0.8% grade

15

v



TABLE I.—MINUTES IN DECIMALS OF A DEGREE.

1'	.0167	11'	.1833	21'	.3500	31'	.5167	41'	.6833	51'	.8500
2	.0333	12	.2000	22	.3667	32	.5333	42	.7000	52	.8667
3	.0500	13	.2167	23	.3833	33	.5500	43	.7167	53	.8833
4	.0667	14	.2333	24	.4000	34	.5667	44	.7333	54	.9000
5	.0833	15	.2500	25	.4167	35	.5833	45	.7500	55	.9167
6	.1000	16	.2667	26	.4333	36	.6000	46	.7667	56	.9333
7	.1167	17	.2833	27	.4500	37	.6167	47	.7833	57	.9500
8	.1333	18	.3000	28	.4667	38	.6333	48	.8000	58	.9667
9	.1500	19	.3167	29	.4833	39	.6500	49	.8167	59	.9833
10	.1667	20	.3333	30	.5000	40	.6667	50	.8333	60	1.0000

TABLE II.—INCHES IN DECIMALS OF A FOOT.

1-16	3-32	¼	3-16	½	5-16	¾	¾	¾	¾	¾
.0052	.0078	.0104	.0156	.0208	.0260	.0313	.0417	.0521	.0625	.0729
1	2	3	4	5	6	7	8	9	10	11
.0833	.1667	.2500	.3333	.4167	.5000	.5833	.6667	.7500	.8333	.9167

TABLE III.—RADI, ORDINATES AND DEFLECTIONS.

Deg.	Radius	Mid. Ord.	Tan. Offset	Def. for 1 Foot	Deg.	Radius	Mid. Ord.	Tan. Offset	Def. for 1 Foot
0° 10'	34377.5	.036	.145	0.05'	7°	819.02	1.528	6.105	2.10'
20	17188.8	.073	.291	0.10	20'	781.84	1.600	6.395	2.20
30	11459.2	.109	.436	0.15	30	764.49	1.637	6.540	2.25
40	8594.42	.145	.582	0.20	40	747.89	1.673	6.685	2.30
50	6875.55	.182	.727	0.25					
1					8	716.78	1.746	6.976	2.40
10	5729.65	.218	.873	0.30	20	688.16	1.819	7.266	2.50
20	4911.15	.255	1.018	0.35	30	674.69	1.855	7.411	2.55
30	4297.28	.291	1.164	0.40	40	661.74	1.892	7.556	2.60
40	3819.83	.327	1.309	0.45					
50	3437.87	.364	1.454	0.50	9	637.28	1.965	7.846	2.70
	3125.36	.400	1.600	0.55	20	614.56	2.037	8.136	2.80
2					30	603.80	2.074	8.281	2.85
10	2864.93	.436	1.745	0.60	40	593.42	2.110	8.426	2.90
20	2644.58	.473	1.891	0.65					
30	2455.70	.509	2.036	0.70	10	573.69	2.183	8.716	3.00
40	2292.01	.545	2.181	0.75	30	546.44	2.292	9.150	3.15
50	2148.79	.582	2.327	0.80	11	521.67	2.402	9.585	3.30
	2022.41	.618	2.472	0.85	30	499.06	2.511	10.02	3.45
3					12	478.34	2.620	10.45	3.60
10	1910.08	.655	2.618	0.90	30	459.28	2.730	10.89	3.75
20	1809.57	.691	2.763	0.95	13	441.68	2.839	11.32	3.90
30	1719.12	.727	2.908	1.00	30	425.40	2.949	11.75	4.05
40	1637.28	.764	3.054	1.05	14	410.28	3.058	12.18	4.20
50	1562.88	.800	3.199	1.10	30	396.20	3.168	12.62	4.35
	1494.95	.836	3.345	1.15					
4					15	383.07	3.277	13.05	4.50
10	1432.69	.873	3.490	1.20	30	370.78	3.387	13.49	4.65
20	1375.40	.909	3.635	1.25	16	359.27	3.496	13.92	4.80
30	1322.53	.945	3.718	1.30	30	348.45	3.606	14.35	4.95
40	1273.57	.982	3.926	1.35	17	338.27	3.716	14.78	5.10
50	1228.11	1.018	4.071	1.40	18	319.62	3.935	15.64	5.40
	1185.78	1.055	4.217	1.45	19	302.94	4.155	16.51	5.70
5					20	287.94	4.374	17.37	6.00
10	1146.28	1.091	4.362	1.50	21	274.37	4.594	18.22	6.30
20	1109.33	1.127	4.507	1.55	22	262.04	4.814	19.08	6.60
30	1074.68	1.164	4.653	1.60	23	250.79	5.035	19.94	6.90
40	1042.14	1.200	4.798	1.65	24	240.49	5.255	20.79	7.20
50	1011.51	1.237	4.943	1.70					
	982.64	1.273	5.088	1.75	25	231.01	5.476	21.64	7.50
6					26	222.27	5.697	22.50	7.80
10	955.37	1.309	5.234	1.80	27	214.18	5.918	23.35	8.10
20	929.57	1.346	5.379	1.85	28	206.68	6.139	24.19	8.40
30	905.13	1.382	5.524	1.90	29	199.70	6.360	25.04	8.70
40	881.95	1.418	5.669	1.95	30	193.18	6.583	25.88	9.00
	859.92	1.455	5.814	2.00					

Note. Chord Deflection=2 times tangent deflection.

TABLE IV.—TANGENTS AND EXTERNALS TO A 1° CURVE.

Central Angle	Tangent	External	Central Angle	Tangent	External	Central Angle	Tangent	External
1°	50.00	.22	11°	551.70	26.50	21°	1061.9	97.57
10'	58.34	.30	10'	560.11	27.31	10'	1070.6	99.16
20	66.67	.39	20	568.53	28.14	20	1079.2	100.75
30	75.01	.49	30	576.95	28.97	30	1087.8	102.35
40	83.34	.61	40	585.36	29.82	40	1096.4	103.97
50	91.68	.73	50	593.79	30.68	50	1105.1	105.60
2	100.01	.87	12	602.21	31.56	22	1113.7	107.24
10	108.35	1.02	10	610.64	32.45	10	1122.4	108.90
20	116.68	1.19	20	619.07	33.35	20	1131.0	110.57
30	125.02	1.36	30	627.50	34.26	30	1139.7	112.25
40	133.36	1.55	40	635.93	35.18	40	1148.4	113.95
50	141.70	1.75	50	644.37	36.12	50	1157.0	115.66
3	150.04	1.96	13	652.81	37.07	23	1165.7	117.38
10	158.38	2.19	10	661.25	38.03	10	1174.4	119.12
20	166.72	2.43	20	669.70	39.01	20	1183.1	120.87
30	175.06	2.67	30	678.15	39.99	30	1191.8	122.63
40	183.40	2.93	40	686.60	40.99	40	1200.5	124.41
50	191.74	3.21	50	695.06	42.00	50	1209.2	126.20
4	200.08	3.49	14	703.51	43.03	24	1217.9	128.00
10	208.43	3.79	10	711.97	44.07	10	1226.6	129.82
20	216.77	4.10	20	720.44	45.12	20	1235.3	131.65
30	225.12	4.42	30	728.90	46.18	30	1244.0	133.50
40	233.47	4.76	40	737.37	47.25	40	1252.8	135.35
50	241.81	5.10	50	745.85	48.34	50	1261.5	137.23
5	250.16	5.46	15	754.32	49.44	25	1270.2	139.11
10	258.51	5.83	10	762.80	50.55	10	1279.0	141.01
20	266.86	6.21	20	771.29	51.68	20	1287.7	142.93
30	275.21	6.61	30	779.77	52.89	30	1296.5	144.85
40	283.57	7.01	40	788.26	53.97	40	1305.3	146.79
50	291.92	7.43	50	796.75	55.13	50	1314.0	148.75
6	300.28	7.86	16	805.25	56.31	26	1322.8	150.71
10	308.64	8.31	10	813.75	57.50	10	1331.6	152.69
20	316.99	8.76	20	822.25	58.70	20	1340.4	154.69
30	325.35	9.23	30	830.76	59.91	30	1349.2	156.70
40	333.71	9.71	40	839.27	61.14	40	1358.0	158.72
50	342.08	10.20	50	847.78	62.38	50	1366.8	160.76
7	350.44	10.71	17	856.30	63.63	27	1375.6	162.81
10	358.81	11.22	10	864.82	64.90	10	1384.4	164.86
20	367.17	11.75	20	873.35	66.18	20	1393.2	166.95
30	375.54	12.29	30	881.88	67.47	30	1402.0	169.04
40	383.91	12.85	40	890.41	68.77	40	1410.9	171.15
50	392.28	13.41	50	898.95	70.09	50	1419.7	173.27
8	400.66	13.99	18	907.49	71.42	28	1428.6	175.41
10	409.03	14.58	10	916.03	72.76	10	1437.4	177.55
20	417.41	15.18	20	924.58	74.12	20	1446.3	179.72
30	425.79	15.80	30	933.13	75.49	30	1455.1	181.89
40	434.17	16.43	40	941.69	76.86	40	1464.0	184.08
50	442.55	17.07	50	950.25	78.26	50	1472.9	186.29
9	450.93	17.72	19	958.81	79.67	29	1481.8	188.51
10	459.32	18.38	10	967.38	81.09	10	1490.7	190.74
20	467.71	19.06	20	975.96	82.53	20	1499.6	192.99
30	476.10	19.75	30	984.53	83.97	30	1508.5	195.25
40	484.49	20.45	40	993.12	85.43	40	1517.4	197.53
50	492.88	21.16	50	1001.7	86.90	50	1526.3	199.82
10	501.28	21.89	20	1010.3	88.39	30	1535.3	202.12
10	509.68	22.62	10	1018.9	89.89	10	1544.2	204.44
20	518.08	23.38	20	1027.5	91.40	20	1553.1	206.77
30	526.48	24.14	30	1036.1	92.92	30	1562.1	209.12
40	534.89	24.91	40	1044.7	94.46	40	1571.0	211.48
50	543.29	25.70	50	1053.3	96.01	50	1580.0	213.86

## IV

TABLE IV.—TANGENTS AND EXTERNALS TO A 1° CURVE.

Central Angle	Tangent	External	Central Angle	Tangent	External	Central Angle	Tangent	External
<b>31°</b>	1589.0	216.3	<b>41°</b>	2142.2	387.4	<b>51°</b>	2732.9	618.4
10'	1598.0	218.7	10'	2151.7	390.7	10'	2743.1	622.8
20	1606.9	221.1	20	2161.2	394.1	20	2753.4	627.2
30	1615.9	223.5	30	2170.8	397.4	30	2763.7	631.7
40	1624.9	226.0	40	2180.3	400.8	40	2773.9	636.2
50	1633.9	228.4	50	2189.9	404.2	50	2784.2	640.7
<b>32</b>	1643.0	230.9	<b>42</b>	2199.4	407.6	<b>52</b>	2794.5	645.2
10	1652.0	233.4	10	2209.0	411.1	10	2804.9	649.7
20	1661.0	235.9	20	2218.6	414.5	20	2815.2	654.3
30	1670.0	238.4	30	2228.1	418.0	30	2825.6	658.8
40	1679.1	241.0	40	2237.7	421.4	40	2835.9	663.4
50	1688.1	243.5	50	2247.3	425.0	50	2846.3	668.0
<b>33</b>	1697.2	246.1	<b>43</b>	2257.0	428.5	<b>53</b>	2856.7	672.7
10	1706.3	248.7	10	2266.6	432.0	10	2867.1	677.3
20	1715.3	251.3	20	2276.2	435.6	20	2877.5	682.0
30	1724.4	253.9	30	2285.9	439.2	30	2888.0	686.7
40	1733.5	256.5	40	2295.6	442.8	40	2898.4	691.4
50	1742.6	259.1	50	2305.2	446.4	50	2908.9	696.1
<b>34</b>	1751.7	261.8	<b>44</b>	2314.9	450.0	<b>54</b>	2919.4	700.9
10	1760.8	264.5	10	2324.6	453.6	10	2929.9	705.7
20	1770.0	267.2	20	2334.3	457.3	20	2940.4	710.5
30	1779.1	269.9	30	2344.1	461.0	30	2951.0	715.3
40	1788.2	272.6	40	2353.8	464.6	40	2961.5	720.1
50	1797.4	275.3	50	2363.5	468.4	50	2972.1	725.0
<b>35</b>	1806.6	278.1	<b>45</b>	2373.3	472.1	<b>55</b>	2982.7	729.9
10	1815.7	280.8	10	2383.1	475.8	10	2993.3	734.8
20	1824.9	283.6	20	2392.8	479.6	20	3003.9	739.7
30	1834.1	286.4	30	2402.6	483.3	30	3014.5	744.6
40	1843.3	289.2	40	2412.4	487.2	40	3025.2	749.6
50	1852.5	292.0	50	2422.3	491.0	50	3035.8	754.6
<b>36</b>	1861.7	294.9	<b>46</b>	2432.1	494.8	<b>56</b>	3046.5	759.6
10	1870.9	297.7	10	2441.9	498.7	10	3057.2	764.6
20	1880.1	300.6	20	2451.8	502.5	20	3067.9	769.7
30	1889.4	303.5	30	2461.7	506.4	30	3078.7	774.7
40	1898.6	306.4	40	2471.5	510.3	40	3089.4	779.8
50	1907.9	309.3	50	2481.4	514.3	50	3100.2	784.9
<b>37</b>	1917.1	312.2	<b>47</b>	2491.3	518.2	<b>57</b>	3110.9	790.1
10	1926.4	315.2	10	2501.2	522.2	10	3121.7	795.2
20	1935.7	318.1	20	2511.2	526.1	20	3132.6	800.4
30	1945.0	321.1	30	2521.1	530.1	30	3143.4	805.6
40	1954.3	324.1	40	2531.1	534.2	40	3154.2	810.9
50	1963.6	327.1	50	2541.0	538.2	50	3165.1	816.1
<b>38</b>	1972.9	330.2	<b>48</b>	2551.0	542.2	<b>58</b>	3176.0	821.4
10	1982.2	333.2	10	2561.0	546.3	10	3186.9	826.7
20	1991.5	336.3	20	2571.0	550.4	20	3197.8	832.0
30	2000.9	339.3	30	2581.0	554.5	30	3208.8	837.3
40	2010.2	342.4	40	2591.0	558.6	40	3219.7	842.7
50	2019.6	345.5	50	2601.1	562.8	50	3230.7	848.1
<b>39</b>	2029.0	348.6	<b>49</b>	2611.2	566.9	<b>59</b>	3241.7	853.5
10	2038.4	351.8	10	2621.2	571.1	10	3252.7	858.9
20	2047.8	354.9	20	2631.3	575.3	20	3263.7	864.3
30	2057.2	358.1	30	2641.4	579.5	30	3274.8	869.8
40	2066.6	361.3	40	2651.5	583.8	40	3285.8	875.3
50	2076.0	364.5	50	2661.6	588.0	50	3296.9	880.8
<b>40</b>	2085.4	367.7	<b>50</b>	2671.8	592.3	<b>60</b>	3308.0	886.4
10	2094.9	371.0	10	2681.9	596.6	10	3319.1	892.0
20	2104.3	374.2	20	2692.1	600.9	20	3330.3	897.5
30	2113.8	377.5	30	2702.3	605.3	30	3341.4	903.2
40	2123.3	380.8	40	2712.5	609.6	40	3352.6	908.8
50	2132.7	384.1	50	2722.7	614.0	50	3363.8	914.5

TABLE IV.—TANGENTS AND EXTERNALS TO A 1° CURVE.

Central Angle	Tangent	External	Central Angle	Tangent	External	Central Angle	Tangent	External
<b>61°</b>	3375.0	920.2	<b>71°</b>	4086.9	1308.2	<b>81°</b>	4893.6	1805.3
10'	3386.3	925.9	10'	4099.5	1315.6	10'	4908.0	1814.7
20	3397.5	931.6	20	4112.1	1322.9	20	4922.5	1824.1
30	3408.8	937.3	30	4124.8	1330.3	30	4937.0	1833.6
40	3420.1	943.1	40	4137.4	1337.7	40	4951.5	1843.1
50	3431.4	948.9	50	4150.1	1345.1	50	4966.1	1852.6
<b>62</b>	3442.7	954.8	<b>72</b>	4162.8	1352.6	<b>82</b>	4980.7	1862.2
10	3454.1	960.6	10	4175.6	1360.1	10	4995.4	1871.8
20	3465.4	966.5	20	4188.5	1367.6	20	5010.0	1881.5
30	3476.8	972.4	30	4201.2	1375.2	30	5024.8	1891.2
40	3488.3	978.3	40	4214.0	1382.8	40	5039.5	1900.9
50	3499.7	984.3	50	4226.8	1390.4	50	5054.3	1910.7
<b>63</b>	3511.1	990.2	<b>73</b>	4239.7	1398.0	<b>83</b>	5069.2	1920.5
10	3522.6	996.2	10	4252.6	1405.7	10	5084.0	1930.4
20	3534.1	1002.3	20	4265.6	1413.5	20	5099.0	1940.3
30	3545.6	1008.3	30	4278.5	1421.2	30	5113.9	1950.3
40	3557.2	1014.4	40	4291.5	1429.0	40	5128.9	1960.2
50	3568.7	1020.5	50	4304.6	1436.8	50	5143.9	1970.3
<b>64</b>	3580.3	1026.6	<b>74</b>	4317.6	1444.6	<b>84</b>	5159.0	1980.4
10	3591.9	1032.8	10	4330.7	1452.5	10	5174.1	1990.5
20	3603.5	1039.0	20	4343.8	1460.4	20	5189.3	2000.6
30	3615.1	1045.2	30	4356.9	1468.4	30	5204.4	2010.8
40	3626.8	1051.4	40	4370.1	1476.4	40	5219.7	2021.1
50	3638.5	1057.7	50	4383.3	1484.4	50	5234.9	2031.4
<b>65</b>	3650.2	1063.9	<b>75</b>	4396.5	1492.4	<b>85</b>	5250.3	2041.7
10	3661.9	1070.2	10	4409.8	1500.5	10	5265.6	2052.1
20	3673.7	1076.6	20	4423.1	1508.6	20	5281.0	2062.5
30	3685.4	1082.9	30	4436.4	1516.7	30	5296.4	2073.0
40	3697.2	1089.3	40	4449.7	1524.9	40	5311.9	2083.5
50	3709.0	1095.7	50	4463.1	1533.1	50	5327.4	2094.1
<b>66</b>	3720.9	1102.2	<b>76</b>	4476.5	1541.4	<b>86</b>	5343.0	2104.7
10	3732.7	1108.6	10	4489.9	1549.7	10	5358.6	2115.3
20	3744.6	1115.1	20	4503.4	1558.0	20	5374.2	2126.0
30	3756.5	1121.7	30	4516.9	1566.3	30	5389.9	2136.7
40	3768.5	1128.2	40	4530.4	1574.7	40	5405.6	2147.5
50	3780.4	1134.8	50	4544.0	1583.1	50	5421.4	2158.4
<b>67</b>	3792.4	1141.4	<b>77</b>	4557.6	1591.6	<b>87</b>	5437.2	2169.2
10	3804.4	1148.0	10	4571.2	1600.1	10	5453.1	2180.2
20	3816.4	1154.7	20	4584.8	1608.6	20	5469.0	2191.1
30	3828.4	1161.3	30	4598.5	1617.1	30	5484.9	2202.2
40	3840.5	1168.1	40	4612.2	1625.7	40	5500.9	2213.2
50	3852.6	1174.8	50	4626.0	1634.4	50	5517.0	2224.3
<b>68</b>	3864.7	1181.6	<b>78</b>	4639.8	1643.0	<b>88</b>	5533.1	2235.5
10	3876.8	1188.4	10	4653.6	1651.7	10	5549.2	2246.7
20	3889.0	1195.2	20	4667.4	1660.5	20	5565.4	2258.0
30	3901.2	1202.0	30	4681.3	1669.2	30	5581.6	2269.3
40	3913.4	1208.9	40	4695.2	1678.1	40	5597.8	2280.6
50	3925.6	1215.8	50	4709.2	1686.9	50	5614.2	2292.0
<b>69</b>	3937.9	1222.7	<b>79</b>	4723.2	1695.8	<b>89</b>	5630.5	2303.5
10	3950.2	1229.7	10	4737.2	1704.7	10	5646.9	2315.0
20	3962.5	1236.7	20	4751.2	1713.7	20	5663.4	2326.6
30	3974.8	1243.7	30	4765.3	1722.7	30	5679.9	2338.2
40	3987.2	1250.8	40	4779.4	1731.7	40	5696.4	2349.8
50	3999.5	1257.9	50	4793.6	1740.8	50	5713.0	2361.5
<b>70</b>	4011.9	1265.0	<b>80</b>	4807.7	1749.9	<b>90</b>	5729.7	2373.3
10	4024.4	1272.1	10	4822.0	1759.0	10	5746.3	2385.1
20	4036.8	1279.3	20	4836.2	1768.2	20	5763.1	2397.0
30	4049.3	1286.5	30	4850.5	1777.4	30	5779.9	2408.9
40	4061.8	1293.6	40	4864.8	1786.7	40	5796.7	2420.9
50	4074.4	1300.9	50	4879.2	1796.0	50	5813.6	2432.9

TABLE IV.—TANGENTS AND EXTERNALS TO A 1° CURVE.

Central Angle	Tangent	External	Central Angle	Tangent	External	Central Angle	Tangent	External
91°	5830.5	2444.9	101°	6950.6	3278.1	111°	8336.7	4386.1
10'	5847.5	2457.1	10'	6971.3	3294.1	10'	8362.7	4407.6
20	5864.6	2469.3	20	6992.0	3310.1	20	8388.9	4429.2
30	5881.7	2481.5	30	7012.7	3326.1	30	8415.1	4450.9
40	5898.8	2493.8	40	7033.6	3342.3	40	8441.5	4472.7
50	5916.0	2506.1	50	7054.5	3358.5	50	8468.0	4494.6
92	5933.2	2518.5	102	7075.5	3374.9	112	8494.6	4516.6
10	5950.5	2531.0	10	7096.6	3391.2	10	8521.3	4538.8
20	5967.9	2543.5	20	7117.8	3407.7	20	8548.1	4561.1
30	5985.3	2556.0	30	7139.0	3424.3	30	8575.0	4583.4
40	6002.7	2568.6	40	7160.3	3440.9	40	8602.1	4606.0
50	6020.2	2581.3	50	7181.7	3457.6	50	8629.3	4628.6
93	6037.8	2594.0	103	7203.2	3474.4	113	8656.6	4651.3
10	6055.4	2606.8	10	7224.7	3491.3	10	8684.0	4674.2
20	6073.1	2619.7	20	7246.3	3508.2	20	8711.5	4697.2
30	6090.8	2632.6	30	7268.0	3525.2	30	8739.2	4720.3
40	6108.6	2645.5	40	7289.8	3542.4	40	8767.0	4743.6
50	6126.4	2658.5	50	7311.7	3559.6	50	8794.9	4766.9
94	6144.3	2671.6	104	7333.6	3576.8	114	8822.9	4790.4
10	6162.6	2684.7	10	7355.6	3594.2	10	8851.0	4814.1
20	6180.2	2697.9	20	7377.8	3611.7	20	8879.3	4837.8
30	6198.3	2711.2	30	7399.9	3629.2	30	8907.7	4861.7
40	6216.4	2724.5	40	7422.2	3646.8	40	8936.3	4885.7
50	6234.6	2737.9	50	7444.6	3664.5	50	8965.0	4909.9
95	6252.8	2751.3	105	7467.0	3682.3	115	8993.8	4934.1
10	6271.1	2764.8	10	7489.6	3700.2	10	9022.7	4958.6
20	6289.4	2778.3	20	7512.2	3718.2	20	9051.7	4983.1
30	6307.9	2792.0	30	7534.9	3736.2	30	9080.9	5007.8
40	6326.3	2805.6	40	7557.7	3754.4	40	9110.3	5032.6
50	6344.8	2819.4	50	7580.5	3772.6	50	9139.8	5057.6
96	6363.4	2833.2	106	7603.5	3791.0	116	9169.4	5082.7
10	6382.1	2847.0	10	7626.6	3809.4	10	9199.1	5107.9
20	6400.8	2861.0	20	7649.7	3827.9	20	9229.0	5133.3
30	6419.5	2875.0	30	7672.9	3846.5	30	9259.0	5158.8
40	6438.4	2889.0	40	7696.3	3865.2	40	9289.2	5184.5
50	6457.3	2903.1	50	7719.7	3884.0	50	9319.5	5210.3
97	6476.2	2917.3	107	7743.2	3902.9	117	9349.9	5236.2
10	6495.2	2931.6	10	7766.8	3921.9	10	9380.5	5262.3
20	6514.3	2945.9	20	7790.5	3940.9	20	9411.3	5288.6
30	6533.4	2960.3	30	7814.3	3960.1	30	9442.2	5315.0
40	6552.6	2974.7	40	7838.1	3979.4	40	9473.2	5341.5
50	6571.9	2989.2	50	7862.1	3998.7	50	9504.4	5368.2
98	6591.2	3003.8	108	7886.2	4018.2	118	9535.7	5395.1
10	6610.6	3018.4	10	7910.4	4037.8	10	9567.2	5422.1
20	6630.1	3033.1	20	7934.6	4057.4	20	9598.9	5449.2
30	6649.6	3047.9	30	7959.0	4077.2	30	9630.7	5476.5
40	6669.2	3062.8	40	7983.5	4097.1	40	9662.6	5504.0
50	6688.8	3077.7	50	8008.0	4117.0	50	9694.7	5531.7
99	6708.6	3092.7	109	8032.7	4137.1	119	9727.0	5559.4
10	6728.4	3107.7	10	8057.4	4157.3	10	9759.4	5587.4
20	6748.2	3122.9	20	8082.3	4177.5	20	9792.0	5615.5
30	6768.1	3138.1	30	8107.3	4197.9	30	9824.8	5643.8
40	6788.1	3153.3	40	8132.3	4218.4	40	9857.7	5672.3
50	5808.2	3168.7	50	8157.5	4239.0	50	9890.8	5700.9
100	6828.3	3184.1	110	8182.8	4259.7	120	9924.0	5729.7
10	6848.5	3199.6	10	8208.2	4280.5	10	9957.5	5758.6
20	6868.8	3215.1	20	8233.7	4301.4	20	9991.0	5787.7
30	6889.2	3230.8	30	8259.3	4322.4	30	10025.0	5817.0
40	6909.6	3246.5	40	8285.0	4343.6	40	10059.0	5846.5
50	6930.1	3262.3	50	8310.8	4364.8	50	10093.0	5876.1

TABLE V.—CORRECTIONS FOR TANGENTS AND EXTERNALS.

These corrections are to be added to the approximate values, found by dividing the tangent, or external, for a 1° curve (Table IV) by the degree of curve, in order to obtain the true tangents, or externals. Intermediate values may be obtained by interpolation.

## FOR TANGENTS ADD

Central Angle	DEGREE OF CURVE													
	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
10°	.03	.06	.09	.13	.16	.19	.22	.25	.28	.31	.34	.38	.42	.46
15°	.04	.10	.14	.19	.24	.29	.34	.39	.45	.51	.53	.58	.63	.68
20°	.06	.13	.19	.26	.32	.39	.45	.51	.58	.65	.72	.79	.84	.90
25°	.08	.16	.24	.33	.40	.49	.58	.67	.75	.83	.90	.99	1.06	1.14
30°	.10	.19	.29	.39	.49	.59	.69	.79	.89	.99	1.09	1.20	1.29	1.39
35°	.11	.22	.34	.47	.58	.69	.79	.81	.92	1.04	1.29	1.42	1.54	1.66
40°	.13	.26	.40	.53	.67	.80	.93	1.06	1.20	1.34	1.49	1.64	1.79	1.94
45°	.15	.30	.44	.60	.76	.91	1.06	1.21	1.37	1.52	1.70	1.87	2.04	2.21
50°	.17	.34	.51	.68	.85	1.02	1.19	1.36	1.54	1.72	1.91	2.10	2.29	2.48
55°	.19	.38	.57	.76	.95	1.14	1.32	1.52	1.72	1.92	2.14	2.35	2.56	2.77
60°	.21	.42	.63	.84	1.05	1.27	1.49	1.71	1.94	2.17	2.38	2.60	2.83	3.07
65°	.23	.46	.69	.93	1.16	1.40	1.64	1.88	2.13	2.38	2.63	2.88	3.13	3.39
70°	.25	.51	.76	1.02	1.28	1.54	1.80	2.06	2.33	2.60	2.88	3.16	3.44	3.72
75°	.27	.56	.83	1.12	1.40	1.69	1.98	2.27	2.57	2.87	3.16	3.47	3.78	4.09
80°	.30	.61	.91	1.22	1.53	1.84	2.15	2.46	2.78	3.10	3.44	3.78	4.12	4.46
85°	.33	.66	1.00	1.33	1.68	2.02	2.36	2.70	3.05	3.40	3.77	4.14	4.55	4.89
90°	.36	.72	1.09	1.45	1.83	2.20	2.57	2.94	3.32	3.70	4.10	4.50	4.91	5.32
95°	.39	.79	1.19	1.55	2.00	2.40	2.80	3.20	3.61	4.02	4.40	4.98	5.38	5.83
100°	.43	.86	1.30	1.74	2.18	2.62	3.06	3.50	3.95	4.40	4.88	5.37	5.85	6.34
110°	.51	1.03	1.56	2.08	2.61	3.14	3.67	4.21	4.76	5.31	5.86	6.43	7.01	7.60
120°	.62	1.25	1.93	2.52	3.16	3.81	4.45	5.11	5.77	6.44	7.12	7.80	8.50	9.22

## FOR EXTERNALS ADD

Central Angle.	DEGREE OF CURVE													
	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
10°	.001	.003	.004	.006	.007	.008	.009	.011	.012	.014	.015	.017	.018	.020
15°	.003	.007	.010	.014	.018	.023	.027	.032	.035	.039	.043	.047	.051	.051
20°	.006	.011	.017	.022	.028	.034	.038	.045	.051	.057	.063	.070	.076	.083
25°	.009	.018	.027	.036	.046	.056	.065	.074	.083	.093	.106	.120	.127	.135
30°	.013	.025	.038	.051	.065	.078	.090	.103	.116	.129	.149	.170	.179	.188
35°	.018	.035	.054	.072	.086	.109	.131	.153	.175	.197	.213	.230	.247	.264
40°	.023	.046	.070	.093	.117	.141	.172	.203	.234	.265	.277	.290	.315	.341
45°	.030	.060	.093	.119	.153	.184	.216	.254	.289	.325	.351	.378	.411	.445
50°	.037	.075	.116	.151	.189	.227	.266	.305	.345	.384	.425	.467	.508	.550
55°	.046	.093	.142	.188	.236	.283	.332	.381	.420	.470	.530	.582	.641	.700
60°	.056	.112	.168	.225	.283	.340	.398	.457	.516	.575	.636	.697	.774	.851
65°	.067	.135	.204	.273	.343	.412	.483	.554	.625	.697	.771	.845	.922	1.01
70°	.080	.159	.240	.321	.403	.485	.568	.652	.735	.819	.906	.994	1.08	1.17
75°	.095	.182	.286	.383	.480	.578	.678	.777	.877	.977	1.07	1.18	1.29	1.39
80°	.110	.220	.332	.445	.558	.671	.787	.903	1.02	1.13	1.25	1.38	1.50	1.62
85°	.128	.259	.391	.524	.657	.790	.926	1.06	1.20	1.34	1.47	1.62	1.76	1.91
90°	.149	.299	.450	.603	.756	.910	1.07	1.22	1.38	1.54	1.70	1.87	2.03	2.20
95°	.174	.350	.522	.706	.885	1.06	1.25	1.43	1.62	1.80	1.99	2.18	2.38	2.58
100°	.200	.401	.604	.809	1.01	1.22	1.43	1.64	1.85	2.06	2.28	2.50	2.73	2.96
110°	.268	.536	.806	1.08	1.35	1.63	1.91	2.20	2.48	2.76	3.05	3.35	3.66	3.96
120°	.360	.721	1.08	1.45	1.82	2.19	2.57	2.95	3.33	3.72	4.11	4.50	4.91	5.32

TABLE VI.--CORRECTIONS FOR SUB-CHORDS AND LONG CHORDS.

FOR SUB-CHORDS ADD										Excess of arc per 100 ft.	LONG CHORDS				
D	10	20	30	40	50	60	70	80	90		D	200	300	400	500
4°	.00	.00	.01	.01	.01	.01	.01	.01	.06	.02	1	199.99	299.97	399.92	499.85
6	.00	.01	.01	.02	.02	.02	.02	.01	.01	.05	2	199.97	299.88	399.70	499.39
8	.01	.02	.02	.03	.03	.03	.03	.02	.01	.08	3	199.93	299.73	399.32	498.63
10	.01	.02	.03	.04	.05	.05	.05	.04	.02	.13	4	199.88	299.51	398.78	497.57
12	.02	.04	.05	.06	.07	.07	.07	.05	.03	.18	5	199.81	299.24	398.10	496.20
14	.02	.05	.07	.08	.09	.10	.09	.07	.04	.25	6	199.73	298.90	397.26	494.53
16	.03	.06	.09	.11	.12	.12	.12	.09	.05	.33	7	199.63	298.51	396.28	492.57
18	.04	.08	.11	.14	.15	.16	.15	.12	.07	.41	8	199.51	298.05	395.14	490.31
20	.05	.10	.14	.17	.19	.20	.18	.15	.09	.51	9	199.38	297.54	393.86	487.75
22	.06	.12	.17	.21	.23	.24	.22	.18	.10	.62	10	199.24	296.96	392.42	484.90
24	.07	.14	.20	.25	.28	.28	.26	.21	.12	.74	12	198.90	295.63	389.12	478.34
26	.09	.17	.24	.29	.32	.33	.31	.25	.15	.86	14	198.51	294.06	385.22	470.65
28	.10	.19	.27	.34	.37	.38	.36	.29	.17	1.00	16	198.05	292.25	380.76	461.86
30	.11	.22	.31	.39	.43	.44	.41	.33	.19	1.15	18	197.54	290.21	375.74	452.02
32	.13	.25	.36	.44	.49	.50	.47	.38	.22	1.31	20	196.96	287.94	370.17	441.15
34	.15	.28	.40	.50	.55	.57	.53	.43	.25	1.48	22	196.32	285.44	364.06	429.30
36	.17	.32	.45	.56	.62	.64	.59	.48	.28	1.66	24	195.63	282.71	357.43	416.53
38	.18	.36	.51	.62	.70	.71	.66	.53	.31	1.86	26	194.87	279.76	350.30	402.89
40	.21	.40	.56	.69	.77	.79	.73	.59	.35	2.06	28	194.06	276.59	342.69	388.43
42	.23	.44	.62	.76	.85	.87	.81	.65	.38	2.28	30	193.18	273.20	334.61	373.20
44	.25	.48	.68	.84	.94	.96	.89	.72	.42	2.50	32	192.25	269.61	326.08	357.23
46	.27	.52	.75	.92	1.02	1.05	.98	.78	.46	2.74	34	191.26	265.81	317.12	340.73
48	.30	.57	.81	1.00	1.12	1.14	1.06	.86	.50	2.99	36	190.21	261.80	307.77	323.61
50	.32	.62	.89	1.09	1.21	1.24	1.15	.93	.55	3.24	38	189.10	257.60	298.03	305.99
52	.35	.67	.96	1.18	1.31	1.35	1.25	1.01	.59	3.52	40	187.94	253.21	287.94	287.94
54	.38	.73	1.04	1.28	1.42	1.46	1.35	1.09	.64	3.80	42	186.72	248.63	277.51	269.54
56	.41	.78	1.12	1.38	1.53	1.57	1.46	1.17	.69	4.09	44	185.44	243.87	266.78	250.85
58	.44	.84	1.20	1.48	1.65	1.69	1.57	1.26	.74	4.40	46	184.10	239.93	255.78	231.95
60	.47	.91	1.29	1.59	1.76	1.81	1.68	1.35	.80	4.72	48	182.71	233.83	244.51	212.92

NOTE.—When a chord of less than 100 ft. is used the corrections given in the above table should be added to the nominal length of chord to get the length which should be used in order that the 100 ft. points will check with those obtained by using the standard 100 ft. chord. Thus in locating a 14° curve by 25 ft. chords measure 25'.06 for each chord. Long chords are useful in passing obstacles.

TABLE VII.--MIDDLE ORDINATES FOR RAILS IN FEET.

Deg. of Curve	LENGTH OF RAILS							Deg. of Curve	LENGTH OF RAILS.						
	32	30	28	26	24	22	20		32	30	28	26	24	22	20
1°	.022	.020	.016	.013	.011	.009	.008	16°	.356	.313	.273	.236	.200	.170	.139
2	.045	.038	.034	.029	.025	.021	.017	17	.378	.333	.290	.252	.213	.180	.148
3	.037	.058	.051	.044	.037	.031	.026	18	.400	.351	.306	.265	.225	.190	.156
4	.089	.079	.069	.060	.050	.042	.035	19	.423	.371	.324	.280	.238	.201	.165
5	.112	.099	.086	.074	.063	.053	.044	20	.445	.392	.341	.296	.250	.212	.174
6	.134	.117	.102	.088	.076	.064	.052	21	.466	.410	.357	.309	.262	.222	.182
7	.156	.137	.120	.104	.088	.074	.061	22	.487	.430	.375	.325	.275	.233	.191
8	.179	.158	.137	.119	.100	.085	.070	23	.509	.450	.390	.338	.287	.243	.199
9	.201	.175	.153	.133	.112	.095	.078	24	.531	.469	.408	.354	.299	.253	.208
10	.223	.196	.171	.148	.125	.106	.087	25	.552	.486	.424	.367	.311	.263	.216
11	.245	.216	.188	.163	.139	.117	.096	26	.573	.506	.441	.382	.323	.274	.225
12	.268	.236	.206	.179	.151	.128	.105	27	.594	.524	.457	.396	.335	.284	.233
13	.290	.254	.222	.192	.163	.138	.113	28	.618	.545	.475	.411	.348	.294	.242
14	.312	.275	.239	.207	.175	.148	.122	29	.638	.564	.491	.424	.361	.303	.250
15	.334	.295	.257	.223	.188	.159	.131	30	.660	.583	.508	.438	.374	.313	.259



## SLOPE REDUCTIONS.

When distances are measured on a slope they may be reduced to the equivalent horizontal distance by the following approximate rule:— subtract from the slope distance the square of the rise divided by twice the slope distance. Thus for a slope distance of 250.3 ft. and a rise of 15 ft. correction =  $15^2 \div 2 \times 250.3 = .45$  (by slide rule) or horizontal distance =  $250.3 - .45 = 249.85$ . When vertical angle = V. A. is measured horizontal distance = slope distance — slope distance (1 — Cos. V. A.). Thus for slope distance of 248.7 ft. and V. A. of  $4^\circ 20'$  from Table VIII Cos = .99714 and correction =  $1 - .99714 = .00286$  per foot or total of  $.286 \times 2\frac{1}{2}$  (near enough) = .57 and horizontal distance =  $248.7 - .57 = 248.13$  ft.

See fig. (a).

## TRIGONOMETRICAL FORMULAS.

$$\begin{aligned} \text{sin.} & A = \frac{a}{c} \\ \text{cos.} & A = \frac{b}{c} \\ \text{tan.} & A = \frac{a}{b} \\ \text{cot.} & A = \frac{b}{a} \\ \text{sec.} & A = \frac{c}{b} \\ \text{cosec.} & A = \frac{c}{a} \end{aligned}$$



## FORMULA FOR SOLVING TRIANGLES.

Given	Sought.	Right triangles. See fig. (a).
$a, c$	$A, B, b$	$\text{sin. } A = \frac{a}{c}, \text{ cos. } B = \frac{a}{c}, b = \sqrt{(c+a)(c-a)}$
$a, b$	$A, B, c$	$\text{tan. } A = \frac{a}{b}, \text{ cot. } B = \frac{a}{b}, c = \sqrt{a^2 + b^2}$
$A, a$	$B, b, c$	$B = 90^\circ - A, b = a \text{ cot. } A, c = \frac{a}{\text{sin. } A}$
$A, b$	$B, a, c$	$B = 90^\circ - A, a = b \text{ tan. } A, c = \frac{b}{\text{cos. } A}$
$A, c$	$B, a, b$	$B = 90^\circ - A, a = c \text{ sin. } A, b = c \text{ cos. } A$
Given	Sought.	Oblique triangles. See fig. (b).
$A, B, a$	$b$	$b = \frac{a \text{ sin. } B}{\text{sin. } A}$
$A, a, b$	$B$	$\text{sin. } B = \frac{b \text{ sin. } A}{a}$
$a, b, C$	$A - B$	$\text{tan. } \frac{1}{2}(A - B) = \frac{(a - b) \text{ tan. } \frac{1}{2}(A + B)}{a + b}$
$a, b, c$	$A$	$\left\{ \begin{aligned} & \text{If } s = \frac{1}{2}(a + b + c), \text{ sin. } \frac{1}{2}A = \sqrt{\frac{(s-b)(s-c)}{bc}} \\ & \text{cos. } \frac{1}{2}A = \sqrt{\frac{s(s-a)}{bc}}, \text{ tan. } \frac{1}{2}A = \sqrt{\frac{(s-b)(s-c)}{s(s-a)}}, \\ & \text{sin. } A = \frac{2\sqrt{s(s-a)(s-b)(s-c)}}{bc} \end{aligned} \right.$
$A, B, C, a$	area	$\text{area} = \frac{a^2 \text{ sin. } B \text{ sin. } C}{2 \text{ sin. } A}$
$A, b, c$	area	$\text{area} = \frac{1}{2} b c \text{ sin. } A$
$a, b, c$	area	$s = \frac{1}{2}(a + b + c), \text{ area} = \sqrt{s(s-a)(s-b)(s-c)}$

TABLE VIII.—NATURAL TRIGONOMETRICAL FUNCTIONS.

Angle	Sine.	Tan.	Cotg.	Cosin.		Angle	Sine.	Tan.	Cotg.	Cosin.	
0	0	0	∞	1	90	8	.1392	.1405	7.115	.99027	82
10	.0029	.0029	343.8	I	50	10	.1421	.1435	6.968	.98986	50
20	.0058	.0058	171.9	.99998	40	20	.1449	.1465	6.827	.98944	40
30	.0087	.0087	114.6	.99996	30	30	.1478	.1495	6.691	.98902	30
40	.0116	.0116	85.94	.99993	20	40	.1507	.1524	6.561	.98858	20
50	.0145	.0145	68.75	.99989	10	50	.1536	.1554	6.435	.98814	10
1	.0175	.0175	57.29	.99985	89	9	.1564	.1584	6.314	.98769	81
10	.0204	.0204	49.10	.99979	50	10	.1593	.1614	6.197	.98723	50
20	.0233	.0233	42.96	.99973	40	20	.1622	.1644	6.084	.98676	40
30	.0262	.0262	38.19	.99966	30	30	.1650	.1673	5.976	.98629	30
40	.0291	.0291	34.37	.99958	20	40	.1679	.1703	5.871	.98580	20
50	.0320	.0320	31.24	.99949	10	50	.1708	.1733	5.769	.98531	10
2	.0349	.0349	28.64	.99939	88	10	.1736	.1763	5.671	.98481	80
10	.0378	.0378	26.43	.99929	50	10	.1765	.1793	5.576	.98430	50
20	.0407	.0407	24.54	.99917	40	20	.1794	.1823	5.485	.98378	40
30	.0436	.0437	22.90	.99905	30	30	.1822	.1853	5.396	.98325	30
40	.0465	.0466	21.47	.99892	20	40	.1851	.1883	5.309	.98272	20
50	.0494	.0495	20.21	.99878	10	50	.1880	.1914	5.226	.98218	10
3	.0523	.0524	19.08	.99863	87	11	.1908	.1944	5.145	.98163	79
10	.0552	.0553	18.07	.99847	50	10	.1937	.1974	5.066	.98107	50
20	.0581	.0582	17.17	.99831	40	20	.1965	.2004	4.989	.98050	40
30	.0610	.0612	16.35	.99813	30	30	.1994	.2035	4.915	.97992	30
40	.0640	.0641	15.60	.99795	20	40	.2022	.2065	4.843	.97934	20
50	.0669	.0670	14.92	.99776	10	50	.2051	.2095	4.773	.97875	10
4	.0698	.0699	14.30	.99756	86	12	.2079	.2126	4.705	.97815	78
10	.0727	.0729	13.73	.99736	50	10	.2108	.2156	4.638	.97754	50
20	.0756	.0758	13.20	.99714	40	20	.2136	.2186	4.574	.97692	40
30	.0785	.0787	12.71	.99692	30	30	.2164	.2217	4.511	.97630	30
40	.0814	.0816	12.25	.99668	20	40	.2193	.2247	4.449	.97566	20
50	.0843	.0846	11.83	.99644	10	50	.2221	.2278	4.390	.97502	10
5	.0872	.0875	11.43	.99619	85	13	.2250	.2309	4.331	.97437	77
10	.0901	.0904	11.06	.99594	50	10	.2278	.2339	4.275	.97371	50
20	.0929	.0934	10.71	.99567	40	20	.2306	.2370	4.219	.97304	40
30	.0958	.0963	10.39	.99540	30	30	.2334	.2401	4.165	.97237	30
40	.0987	.0992	10.08	.99511	20	40	.2363	.2432	4.113	.97169	20
50	.1016	.1022	9.788	.99482	10	50	.2391	.2462	4.061	.97100	10
6	.1045	.1051	9.514	.99452	84	14	.2419	.2493	4.011	.97030	76
10	.1074	.1080	9.255	.99421	50	10	.2447	.2524	3.962	.96959	50
20	.1103	.1110	9.010	.99390	40	20	.2476	.2555	3.914	.96887	40
30	.1132	.1139	8.777	.99357	30	30	.2504	.2586	3.867	.96815	30
40	.1161	.1169	8.556	.99324	20	40	.2532	.2617	3.821	.96742	20
50	.1190	.1198	8.345	.99290	10	50	.2560	.2648	3.776	.96667	10
7	.1219	.1228	8.144	.99255	83	15	.2588	.2679	3.732	.96593	75
10	.1248	.1257	7.953	.99219	50	10	.2616	.2711	3.689	.96517	50
20	.1276	.1287	7.770	.99182	40	20	.2644	.2742	3.647	.96440	40
30	.1305	.1317	7.596	.99144	30	30	.2672	.2773	3.606	.96363	30
40	.1334	.1346	7.429	.99106	20	40	.2700	.2805	3.566	.96285	20
50	.1363	.1376	7.269	.99067	10	50	.2728	.2836	3.526	.96206	10
					82						74
	Cosin.	Cotg.	Tan.	Sine.	Angle.		Cosin.	Cotg.	Tan.	Sine.	Angle.

TABLE VIII.—NATURAL TRIGONOMETRICAL FUNCTIONS.

Angle	Sine.	Tan.	Cotg.	Cosin.		Angle	Sine.	Tan.	Cotg.	Cosin.	
<i>or</i> 16	.2756	.2867	3.487	.96126	74	<i>or</i> 24	.4067	.4452	2.246	.91355	66
10	.2784	.2899	3.450	.96046	50	10	.4094	.4487	2.229	.91236	50
20	.2812	.2931	3.412	.95964	40	20	.4120	.4522	2.211	.91116	40
30	.2840	.2962	3.376	.95882	30	30	.4147	.4557	2.194	.90996	30
40	.2868	.2994	3.340	.95799	20	40	.4173	.4592	2.177	.90875	20
50	.2896	.3026	3.305	.95715	10	50	.4200	.4628	2.161	.90753	10
<b>17</b>	.2924	.3057	3.271	.95615	<b>73</b>	<b>25</b>	.4226	.4663	2.145	.90631	<b>65</b>
10	.2952	.3089	3.237	.95545	50	10	.4253	.4699	2.128	.90507	50
20	.2979	.3121	3.204	.95459	40	20	.4279	.4734	2.112	.90383	40
30	.3007	.3153	3.172	.95372	30	30	.4305	.4770	2.097	.90259	30
40	.3035	.3185	3.140	.95284	20	40	.4331	.4806	2.081	.90133	20
50	.3062	.3217	3.108	.95195	10	50	.4358	.4841	2.066	.90007	10
<b>18</b>	.3090	.3249	3.078	.95106	<b>72</b>	<b>26</b>	.4384	.4877	2.050	.89879	<b>64</b>
10	.3118	.3281	3.048	.95015	50	10	.4410	.4913	2.035	.89752	50
20	.3145	.3314	3.018	.94924	40	20	.4436	.4950	2.020	.89623	40
30	.3173	.3346	2.989	.94832	30	30	.4462	.4986	2.006	.89493	30
40	.3201	.3378	2.960	.94740	20	40	.4488	.5022	1.991	.89363	20
50	.3228	.3411	2.932	.94646	10	50	.4514	.5059	1.977	.89232	10
<b>19</b>	.3256	.3443	2.904	.94552	<b>71</b>	<b>27</b>	.4540	.5095	1.963	.89101	<b>63</b>
10	.3283	.3476	2.877	.94457	50	10	.4566	.5132	1.949	.88968	50
20	.3311	.3508	2.850	.94361	40	20	.4592	.5169	1.935	.88835	40
30	.3338	.3541	2.824	.94264	30	30	.4617	.5206	1.921	.88701	30
40	.3365	.3574	2.798	.94167	20	40	.4643	.5243	1.907	.88566	20
50	.3393	.3607	2.773	.94068	10	50	.4669	.5280	1.894	.88431	10
<b>20</b>	.3420	.3640	2.747	.93969	<b>70</b>	<b>28</b>	.4695	.5317	1.881	.88295	<b>62</b>
10	.3448	.3673	2.723	.93869	50	10	.4720	.5354	1.868	.88158	50
20	.3475	.3706	2.669	.93769	40	20	.4746	.5392	1.855	.88020	40
30	.3502	.3739	2.675	.93667	30	30	.4772	.5430	1.842	.87882	30
40	.3529	.3772	2.651	.93565	20	40	.4797	.5467	1.829	.87743	20
50	.3557	.3805	2.628	.93462	10	50	.4823	.5505	1.816	.87603	10
<b>21</b>	.3584	.3839	2.605	.93358	<b>69</b>	<b>29</b>	.4848	.5543	1.804	.87462	<b>61</b>
10	.3611	.3872	2.583	.93253	50	10	.4874	.5581	1.792	.87321	50
20	.3638	.3906	2.560	.93148	40	20	.4899	.5619	1.780	.87178	40
30	.3665	.3939	2.539	.93042	30	30	.4924	.5658	1.767	.87036	30
40	.3692	.3973	2.517	.92935	20	40	.4950	.5696	1.756	.86892	20
50	.3719	.4006	2.496	.92827	10	50	.4975	.5735	1.744	.86748	10
<b>22</b>	.3746	.4040	2.475	.92718	<b>68</b>	<b>30</b>	.5000	.5774	1.732	.86603	<b>60</b>
10	.3773	.4074	2.455	.92609	50	10	.5025	.5812	1.720	.86457	50
20	.3800	.4108	2.434	.92499	40	20	.5050	.5851	1.709	.86310	40
30	.3827	.4142	2.414	.92388	30	30	.5075	.5890	1.698	.86163	30
40	.3854	.4176	2.394	.92276	20	40	.5100	.5930	1.686	.86015	20
50	.3881	.4210	2.375	.92164	10	50	.5125	.5969	1.675	.85866	10
<b>23</b>	.3907	.4245	2.356	.92050	<b>67</b>	<b>31</b>	.5150	.6009	1.664	.85717	<b>59</b>
10	.3934	.4279	2.337	.91936	50	10	.5175	.6048	1.653	.85567	50
20	.3961	.4314	2.318	.91822	40	20	.5200	.6088	1.643	.85416	40
30	.3987	.4348	2.300	.91706	30	30	.5225	.6128	1.632	.85264	30
40	.4014	.4383	2.282	.91590	20	40	.5250	.6168	1.621	.85112	20
50	.4041	.4417	2.264	.91472	10	50	.5275	.6208	1.611	.84959	10
					66						58
	Cosin.	Cotg.	Tan.	Sine.	Angle.		Cosin.	Cotg.	Tan.	Sine.	Angle.

TABLE VIII.—NATURAL TRIGONOMETRICAL FUNCTIONS.

Angle	Sine.	Tan.	Cotg.	Cosin.		Angle	Sine.	Tan.	Cotg.	Cosin.	
°						°					
32	.5299	.6249	1.600	.84805	58	30	.6225	.7954	1.257	.78261	
10	.5324	.6289	1.590	.84650	50	40	.6248	.8002	1.250	.78079	
20	.5348	.6330	1.580	.84495	40	50	.6271	.8050	1.242	.77897	
30	.5373	.6371	1.570	.84339	30	39	.6293	.8098	1.235	.77715	
40	.5398	.6412	1.560	.84182	20	10	.6316	.8146	1.228	.77531	
50	.5422	.6453	1.550	.84025	10	20	.6338	.8195	1.220	.77347	
33	.5446	.6494	1.540	.83867	57	30	.6361	.8243	1.213	.77162	
10	.5471	.6536	1.530	.83708	50	40	.6383	.8292	1.206	.76977	
20	.5495	.6577	1.520	.83549	40	50	.6406	.8342	1.199	.76791	
30	.5519	.6619	1.511	.83389	30	40	.6428	.8391	1.192	.76604	
40	.5544	.6661	1.501	.83228	20	10	.6450	.8441	1.185	.76417	
50	.5568	.6703	1.492	.83066	10	20	.6472	.8491	1.178	.76229	
34	.5592	.6745	1.483	.82904	56	30	.6494	.8541	1.171	.76041	
10	.5616	.6787	1.473	.82741	50	40	.6517	.8591	1.164	.75851	
20	.5640	.6830	1.464	.82577	40	50	.6539	.8642	1.157	.75661	
30	.5664	.6873	1.455	.82413	30	41	.6561	.8693	1.150	.75471	
40	.5688	.6916	1.446	.82248	20	10	.6583	.8744	1.144	.75280	
50	.5712	.6959	1.437	.82082	10	20	.6604	.8796	1.137	.75088	
35	.5736	.7002	1.428	.81915	55	30	.6626	.8847	1.130	.74896	
10	.5760	.7046	1.419	.81748	50	40	.6648	.8899	1.124	.74703	
20	.5783	.7089	1.411	.81580	40	50	.6670	.8952	1.117	.74509	
30	.5807	.7133	1.402	.81412	30	42	.6691	.9004	1.111	.74314	
40	.5831	.7177	1.393	.81242	20	10	.6713	.9057	1.104	.74120	
50	.5854	.7221	1.385	.81072	10	20	.6734	.9110	1.098	.73924	
36	.5878	.7265	1.376	.80902	54	30	.6756	.9163	1.091	.73728	
10	.5901	.7310	1.368	.80730	50	40	.6777	.9217	1.085	.73531	
20	.5925	.7355	1.360	.80558	40	50	.6799	.9271	1.079	.73333	
30	.5948	.7400	1.351	.80386	30	43	.6820	.9325	1.072	.73135	
40	.5972	.7445	1.343	.80212	20	10	.6841	.9380	1.066	.72937	
50	.5995	.7490	1.335	.80038	10	20	.6862	.9435	1.060	.72737	
37	.6018	.7536	1.327	.79864	53	30	.6884	.9490	1.054	.72537	
10	.6041	.7581	1.319	.79688	50	40	.6905	.9545	1.048	.72337	
20	.6065	.7627	1.311	.79512	40	50	.6926	.9601	1.042	.72136	
30	.6088	.7673	1.303	.79335	30	44	.6947	.9657	1.036	.71934	
40	.6111	.7720	1.295	.79158	20	10	.6967	.9713	1.030	.71732	
50	.6134	.7766	1.288	.78980	10	20	.6988	.9770	1.024	.71529	
38	.6157	.7813	1.280	.78801	52	30	.7009	.9827	1.018	.71325	
10	.6180	.7860	1.272	.78622	50	40	.7030	.9884	1.012	.71121	
20	.6202	.7907	1.265	.78442	40	50	.7050	.9942	1.006	.70916	
							.7071	1.	1.	.70711	
										°	
	Cosin.	Cotg.	Tan.	Sine.	Angle.		Cosin.	Cotg.	Tan.	Sine.	Angle.

TABLE IX.—CALCULATION OF EARTHWORK.


Width	HEIGHT														
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
1	.02	.04	.06	.07	.09	.11	.13	.15	.17	.18	.20	.22	.24	.26	.28
2	.04	.07	.11	.15	.18	.22	.26	.30	.33	.37	.41	.44	.48	.52	.56
3	.06	.11	.17	.22	.28	.33	.39	.44	.50	.56	.61	.67	.72	.78	.83
4	.07	.15	.22	.30	.37	.44	.52	.59	.67	.74	.81	.89	.96	1.04	1.11
5	.09	.19	.28	.37	.46	.56	.65	.74	.83	.93	1.02	1.11	1.20	1.30	1.39
6	.11	.22	.33	.44	.56	.67	.78	.89	1.00	1.11	1.22	1.33	1.44	1.55	1.67
7	.13	.26	.39	.52	.65	.78	.91	1.04	1.16	1.30	1.42	1.55	1.68	1.81	1.94
8	.15	.30	.44	.59	.74	.89	1.04	1.19	1.33	1.48	1.63	1.78	1.92	2.08	2.22
9	.17	.33	.50	.67	.83	1.00	1.17	1.33	1.50	1.67	1.83	2.00	2.17	2.33	2.50
10	.18	.37	.56	.74	.93	1.11	1.30	1.48	1.67	1.85	2.04	2.22	2.41	2.59	2.78
11	.20	.41	.61	.82	1.02	1.22	1.43	1.63	1.83	2.04	2.24	2.44	2.65	2.85	3.06
12	.22	.44	.67	.89	1.11	1.33	1.56	1.78	2.00	2.22	2.44	2.67	2.89	3.11	3.33
13	.24	.48	.72	.96	1.20	1.44	1.68	1.92	2.16	2.41	2.65	2.89	3.13	3.37	3.61
14	.26	.52	.78	1.04	1.30	1.55	1.81	2.08	2.33	2.59	2.85	3.11	3.37	3.63	3.89
15	.28	.56	.83	1.11	1.39	1.67	1.94	2.22	2.50	2.78	3.06	3.33	3.61	3.89	4.17
16	.30	.59	.89	1.18	1.48	1.78	2.07	2.37	2.67	2.96	3.26	3.56	3.85	4.15	4.44
17	.31	.63	.94	1.26	1.57	1.89	2.20	2.52	2.83	3.15	3.46	3.78	4.09	4.41	4.72
18	.33	.67	1.00	1.33	1.67	2.00	2.33	2.67	3.00	3.33	3.67	4.00	4.33	4.67	5.00
19	.35	.70	1.06	1.41	1.76	2.11	2.46	2.82	3.17	3.52	3.87	4.22	4.57	4.92	5.28
20	.37	.74	1.11	1.48	1.85	2.22	2.59	2.96	3.33	3.70	4.07	4.44	4.81	5.18	5.56
21	.39	.78	1.17	1.55	1.94	2.33	2.72	3.11	3.50	3.89	4.28	4.67	5.06	5.44	5.83
22	.41	.81	1.22	1.63	2.04	2.44	2.85	3.26	3.67	4.07	4.48	4.89	5.30	5.70	6.11
23	.43	.85	1.28	1.70	2.13	2.56	2.98	3.41	3.83	4.26	4.68	5.11	5.54	5.96	6.39
24	.44	.89	1.33	1.78	2.22	2.67	3.11	3.56	4.00	4.44	4.89	5.33	5.78	6.22	6.67
25	.46	.92	1.39	1.85	2.31	2.78	3.24	3.70	4.17	4.63	5.09	5.56	6.02	6.48	6.94
26	.48	.96	1.44	1.92	2.41	2.89	3.37	3.85	4.33	4.82	5.30	5.78	6.26	6.74	7.24
27	.50	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
28	.52	1.04	1.55	2.07	2.59	3.11	3.63	4.15	4.67	5.18	5.70	6.22	6.74	7.26	7.78
29	.54	1.07	1.61	2.15	2.68	3.22	3.76	4.30	4.83	5.37	5.91	6.44	6.98	7.52	8.06
30	.56	1.11	1.67	2.22	2.78	3.33	3.89	4.44	5.00	5.55	6.11	6.67	7.22	7.78	8.33
31	.57	1.15	1.72	2.30	2.87	3.44	4.02	4.59	5.17	5.74	6.32	6.89	7.46	8.04	8.61
32	.59	1.18	1.78	2.37	2.96	3.56	4.15	4.74	5.33	5.92	6.52	7.11	7.70	8.30	8.89
33	.61	1.22	1.83	2.44	3.05	3.67	4.28	4.89	5.50	6.11	6.72	7.33	7.94	8.55	9.17
34	.63	1.26	1.89	2.52	3.15	3.78	4.40	5.04	5.67	6.29	6.93	7.56	8.18	8.81	9.44
35	.65	1.30	1.94	2.59	3.24	3.89	4.53	5.18	5.83	6.48	7.13	7.78	8.42	9.08	9.72
36	.67	1.33	2.06	2.67	3.33	4.00	4.66	5.33	6.00	6.67	7.33	8.00	8.67	9.33	10.00
37	.68	1.37	2.06	2.74	3.42	4.11	4.79	5.48	6.17	6.85	7.54	8.22	8.91	9.59	10.28
38	.70	1.41	2.11	2.82	3.52	4.22	4.92	5.63	6.33	7.03	7.74	8.44	9.15	9.85	10.56
39	.72	1.44	2.17	2.89	3.61	4.33	5.05	5.78	6.50	7.22	7.95	8.67	9.39	10.11	10.83
40	.74	1.48	2.22	2.96	3.70	4.44	5.18	5.92	6.67	7.41	8.15	8.89	9.63	10.37	11.11


Table gives cu. yds. in 1 ft. of a triangle of given width and height. Corrections for tenths of width are one tenth the values found under each height considering the widths from 1 to 9 as tenths and similarly the corrections for tenths of height are one tenth the figures opposite width considering the heights from 1 to 9 as tenths. Thus if  $w=16.2$  and  $h=5.3$ , cu. yds.  $=1.48+.028+.089=1.597$  cu. yds. or practically 160 cu. yds. per 100 ft. If  $w$  exceeds 40 ft., use one half and multiply result by 2, if both  $w$  and  $h$  are large use one half of each and multiply result by 4. Any cross-section may be divided into triangles by the following rule. To the triangle of the sum of the outside cuts (or fills)  $=h$ , and  $\frac{1}{2}$  the roadbed  $=w$ , add the triangles formed by taking the distance out to each break in 'turn' ( $=w$ 's) by the difference between the cuts (or fills) on each side of it ( $=h$ 's) always subtracting the outer from the inner.

## DIAGRAM FOR OBTAINING HORIZONTAL AND VERTICAL DISTANCES FROM STADIA READINGS


Enter on the horizontal scale with the value of the stadia reading or interval times the stadia constant (usually taken as 100) and run vertically upward to intersection with line representing the vertical angle. The location of this point with reference to the dotted line marked "ONE," etc., gives the correction to be subtracted from the entering value and to which "f+c" (usually about 1 ft.) must be added to obtain the Horizontal Distance. The reading on vertical scale plus about 0.1 ft. for each 5° of vertical angle  $[-(f+c \sin \alpha)]$  is the Vertical Distance.


© 1944 BY J.K.FINCH.





STADIA READING X STADIA CONSTANT





U 2446

Notes for

$\Sigma$  Jobs in

1 book. —

**DISTANCES FROM CENTER OF ROADWAY FOR  
CROSS-SECTIONING.**

Roadway 16 feet wide. Side Slopes 1 on 1½.  
For Single Track Embankment.

H	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	H
0	8.0	8.2	8.3	8.5	8.6	8.8	8.9	9.1	9.2	9.4	0
1	9.5	9.7	9.8	10.0	10.1	10.3	10.4	10.6	10.7	10.9	1
2	11.0	11.2	11.3	11.5	11.6	11.8	11.9	12.1	12.2	12.4	2
3	12.5	12.7	12.8	13.0	13.1	13.3	13.4	13.6	13.7	13.9	3
4	14.0	14.2	14.3	14.5	14.6	14.8	14.9	15.1	15.2	15.4	4
5	15.5	15.7	15.8	16.0	16.1	16.3	16.4	16.6	16.7	16.9	5
6	17.0	17.2	17.3	17.5	17.6	17.8	17.9	18.1	18.2	18.4	6
7	18.5	18.7	18.8	19.0	19.1	19.3	19.4	19.6	19.7	19.9	7
8	20.0	20.2	20.3	20.5	20.6	20.8	20.9	21.1	21.2	21.4	8
9	21.5	21.7	21.8	22.0	22.1	22.3	22.4	22.6	22.7	22.9	9
10	23.0	23.2	23.3	23.5	23.6	23.8	23.9	24.1	24.2	24.4	10
11	24.5	24.7	24.8	25.0	25.1	25.3	25.4	25.6	25.7	25.9	11
12	26.0	25.2	26.3	26.5	26.6	26.8	26.9	27.1	27.2	27.4	12
13	27.5	27.7	27.8	28.0	28.1	28.3	28.4	28.6	28.7	28.9	13
14	29.0	29.2	29.3	29.5	29.6	29.8	29.9	30.1	30.2	30.4	14
15	30.5	30.7	30.8	31.0	31.1	31.3	31.4	31.6	31.7	31.9	15
16	32.0	32.2	32.3	32.5	32.6	32.8	32.9	33.1	33.2	33.4	16
17	33.5	33.7	33.8	34.0	34.1	34.3	34.4	34.6	34.7	34.9	17
18	35.0	35.2	35.3	35.5	35.6	35.8	35.9	36.1	36.2	36.4	18
19	36.5	36.7	36.8	37.0	37.1	37.3	37.4	37.6	37.7	37.9	19
20	38.0	38.2	38.3	38.5	38.6	38.8	38.9	39.1	39.2	39.4	20
21	39.5	39.7	39.8	40.0	40.1	40.3	40.4	40.6	40.7	40.9	21
22	41.0	41.2	41.3	41.5	41.6	41.8	41.9	42.1	42.2	42.4	22
23	42.5	42.7	42.8	43.0	43.1	43.3	43.4	43.6	43.7	43.9	23
24	44.0	44.2	44.3	44.5	44.6	44.8	44.9	45.1	45.2	45.4	24
25	45.5	45.7	45.8	46.0	46.1	46.3	46.4	46.6	46.7	46.9	25
26	47.0	47.2	47.3	47.5	47.6	47.8	47.9	48.1	48.2	48.4	26
27	48.5	48.7	48.8	49.0	49.1	49.3	49.4	49.6	49.7	49.9	27
28	50.0	50.2	50.3	50.5	50.6	50.8	50.9	51.1	51.2	51.4	28
29	51.5	51.7	51.8	52.0	52.1	52.3	52.4	52.6	52.7	52.9	29
30	53.0	53.2	53.3	53.5	53.6	53.8	53.9	54.1	54.2	54.4	30
31	54.5	54.7	54.8	55.0	55.1	55.3	55.4	55.6	55.7	55.9	31
32	56.0	56.2	56.3	56.5	56.6	56.8	56.9	57.1	57.2	57.4	32
33	57.5	57.7	57.8	58.0	58.1	58.3	58.4	58.6	58.7	58.9	33
34	59.0	59.2	59.3	59.5	59.6	59.8	59.9	60.1	60.2	60.4	34
35	60.5	60.7	60.8	61.0	61.1	61.3	61.4	61.6	61.7	61.9	35
36	62.0	62.2	62.3	62.5	62.6	62.8	62.9	63.1	63.2	63.4	36
37	63.5	63.7	63.8	64.0	64.1	64.3	64.4	64.6	64.7	64.9	37
38	65.0	65.2	65.3	65.5	65.6	65.8	65.9	66.1	66.2	66.4	38
39	66.5	66.7	66.8	67.0	67.1	67.3	67.4	67.6	67.7	67.9	39
40	68.0	68.2	68.3	68.5	68.6	68.8	68.9	69.1	69.2	69.4	40

**Example**—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 41.9. For same slopes but other widths of roadbed correct above figures by one-half difference in width of roadbed; thus in example above for 20 ft. roadbed distance will be  $41.9 + (20 - 16) \div 2$  or 2 ft. added to 41.9 = 43.9. For slopes of 1 on 1 see inside of front cover.